



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Asus A7M266-D Motherboard, AMD Athlon (TM) MP 2000+

SPECfp2000 = 596

SPECfp_base2000 = 548

SPEC license #: 49 Tested by: AMD Austin TX Test date: Feb-2002 Hardware Avail: Jan-2002 Software Avail: Feb-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	198	807	198	809	
171.swim	3100	374	829	366	846	
172.mgrid	1800	347	518	337	534	
173.applu	2100	435	483	426	493	
177.mesa	1400	158	886	157	892	
178.galgel	2900	593	489	330	880	
179.art	2600	663	392	629	414	
183.quake	1300	268	485	224	581	
187.facerec	1900	307	618	306	620	
188.amp	2200	559	393	519	424	
189.lucas	2000	350	572	346	577	
191.fma3d	2100	343	611	342	614	
200.sixtrack	1100	262	420	255	431	
301.apsi	2600	590	441	502	518	

Hardware

CPU: AMD Athlon (TM) MP 2000+
 CPU MHz: 1667
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 2x256MB PC2100 DDR SDRAM CL2
 Disk Subsystem: Seagate ST318451LW
 Other Hardware: None

Software

Operating System: Windows 2000 SP2
 Compiler: Intel C++ 5.0.1 build 020125Z
 Intel Fortran 5.0.1 build 020125Z and Compaq Visual Fortran 6.6
 Microsoft Visual Studio 6.0 SP5 (libraries)
 MicroQuill Smartheap Library 5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
 icl and ifl are the Intel C++ and Fortran compilers
 f90 is the Compaq Fortran compiler
 shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
 Portability:
 178.galgel: -FI -Fe\$@ -link -stack:32000000
 Baseline: C icl -QxK -Qipo +FDO shlw32M.lib
 Baseline: Fortran ifl -O3 -QxK -Qipo +FDO
 Peak tuning:
 168.wupwise: ifl -O3 -QxK -Qwp_ipo +FDO
 171.swim: ifl -O3 -QxK -Qwp_ipo +FDO
 172.mgrid: ifl -O3 -QxK -Qwp_ipo +FDO
 173.applu: ifl -O3 -QxK -Qwp_ipo -Qscalar_rep- -Qauto +FDO
 177.mesa: icl -O3 -QxK -Qwp_ipo -Oa +FDO shlw32M.lib
 178.galgel: f90 -Optimize:5 -fast
 179.art: icl -O3 -QxK -QaxW -Qwp_ipo -Oa +FDO shlw32M.lib
 183.quake: icl -O3 -QxK -Qwp_ipo -Qrcd -Oa +FDO shlw32M.lib



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Asus A7M266-D Motherboard, AMD Athlon (TM) MP 2000+

SPECfp2000 = 596

SPECfp_base2000 = 548

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Feb-2002 | Hardware Avail: Jan-2002 | Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```
187.facerec: ifl -O3 -QxK -Qipo +FDO
188.ammf:    icl -O3 -QxK -Qwp_ipo -Oa +FDO
189.lucas:   ifl -O3 -QxK -Qwp_ipo +FDO shlw32M.lib
191.fma3d:   ifl -O3 -QxK -Qwp_ipo +FDO
200.sixtrack: ifl -QxK -QaxW -Qwp_ipo -Qprefetch +FDO
301.apsi:    f90 -Optimize:5 -fast
```

Library ordering for 189.lucas (to include SmartHeap correctly with default libs):

```
LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
ONESTEP is used for all base and peak runs
```

The tested system can be assembled using an ATX case such as the Antec KS-282, a 420W power supply such as the NSpire MSP-420P4B, and a PCI or AGP video card. The System bus runs at 266MHz