



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER200 (700MHz)

SPECint_rate2000 = 10.9
SPECint_rate_base2000 = 9.35

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Jul-2002 Hardware Avail: Aug-2002 Software Avail: May-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	350	9.27	2	306	10.6
175.vpr	2	364	8.93	2	350	9.29
176.gcc	2	441	5.79	2	246	10.4
181.mcf	2	553	7.55	2	474	8.81
186.crafty	2	260	8.92	2	174	13.3
197.parser	2	423	9.87	2	409	10.2
252.eon	2	245	12.3	2	220	13.7
253.perlbnk	2	379	11.0	2	323	12.9
254.gap	2	428	5.97	2	419	6.10
255.vortex	2	305	14.5	2	283	15.6
256.bzip2	2	347	10.0	2	347	10.0
300.twolf	2	581	12.0	2	505	13.8

Hardware

CPU: SPARC64 GP
CPU MHz: 700
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1 to 2
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 4MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 8192MB
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01.
Sun ONE Studio 7 with current patches (see notes)
Sun Performance Library 7
File System: ufs
System State: single user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
fdo_pre0=rm -rf `pwd`/*.fbk
PASS1=-Kpg
PASS2=-Kpu=\$(EXEBASE).fbk
(252.eon, for Sun ONE Studio 7): -fast -xcrossfile -xtarget=ultra3
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback

Peak

(for Sun ONE Studio 7)
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
164.gzip: -x05 -xtarget=ultra3 -xalias_level=std -W2,-whole -xcrossfile
-W2,-Ainline -xprefetch -Wc,-Qgsched-trace_late=1,-Qgsched-spec_load=1 -l12amm
176.gcc: -fast -xtarget=ultra3 -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -l12amm
186.crafty: -fast -xtarget=ultra3 -xarch=v8plus -xP -xinline=-xcrossfile -Wc,-Qgsched-spec_load=1,-Qiselect-funcalign=64
-xalias_level=strong -xregs=syst -W2,-Ashort_ldst,-Aivel:duplicate_loops -xprefetch=auto,latx:5.0
197.parser: -fast -xarch=v8plusb -xdepend -xprefetch=no%auto -xcrossfile



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER200 (700MHz)

SPECint_rate2000 = 10.9
SPECint_rate_base2000 = 9.35

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jul-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```

-xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
-Wc,-Qipa:valueprediction -W2,-Ashort_ldst,-Mt5000 -Wc,-Qiselect-funcalign=32 -lprism32
252.eon: -fast -xtarget=ultra3 -xcrossfile -xalias_level=compatible -xsafe=mem -Qoption iropt
-Mt2000,-xrestrict -Qoption cg -Qgsched-trace_spec_load=1,-Qgsched-trace_late=1
253.perlbnk: -x05 -xtarget=ultra3 -xarch=v8plusb -xcrossfile -xalias_level=strong -xsafe=mem -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1
-Wc,-Qinline_memcpy=32 -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1
-Wc,-Qiselect-sw_pf_tbl_th=20 -W2,-Adata_access -xprefetch=auto,latx:5.0 -l12amm -dn
255.vortex: -fast -xtarget=ultra3 -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Msl,-Mt600,-Mr13000,-crit
-Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
-xrestrict -xdepend -W2,-Amemopt -l12amm -lprism32

```

(for Parallelnavi 1.0.2):

fdo_pre0=rm -rf `pwd`/*.fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

175.vpr: -Kfast_GP=4,staticclump,eval,preex,popt,switchopt,cond,GREG,nounroll,largepage,NOFLTLD=5,fconst,xi=30

181.mcf: -Kfast_GP=2,GREG,eval,preex,popt,unroll=2,prefetch=4,largepage,preload -x-

254.gap: -Kfast_GP=3,popt,eval,cfunc,largepage,xi=10

256.bzip2: basepeak=yes

300.twolf: -Kfast_GP=5,eval,GREG,popt,cfunc,staticclump,use_rodata,xi=10,largepage,bcopy,nounroll,prefetch=4

Portability:

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSUN

252.eon: -library=iostream

253.perlbnk: -DSPEC_CPU2000_SOLARIS

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=4G, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"

LD_LIBRARY_PATH_64="/usr/lib/64:/opt/SUNWspro/lib/v9:/opt/SUNWspro/prod/lib/v9"

PRISM_HEAP=268435456

PRISM_MODE=2

ONESTEP=yes was set for all baseline and peak benchmarks.

Feedback directed optimization was used for all baseline and peak benchmarks.

System board used with only one CPU present.

All patches of Sun ONE Studio 7 posted at URL <http://access1.sun.com/sundev/s1s7-patches.html>

as of date 2002/6/4 were applied: 111704-01, 111705-01, 111706-01,

111708-01, 111709-01, 111715-01, 111716-01.