



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1500MHz, Itanium 2)

SPECint_rate2000 = --
SPECint_rate_base2000 = 227

SPEC license #: 4 | Tested by: SGI | Test date: Jan-2004 | Hardware Avail: Jul-2003 | Software Avail: Dec-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	154	169			
175.vpr	16	135	193			
176.gcc	16	88.0	232			
181.mcf	16	96.2	347			
186.crafty	16	83.6	222			
197.parser	16	192	174			
252.eon	16	86.2	280			
253.perlbnk	16	152	220			
254.gap	16	132	154			
255.vortex	16	97.9	360			
256.bzip2	16	130	214			
300.twolf	16	221	252			

Hardware

CPU: Intel Itanium 2
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 4-64
Parallel: No
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 6.0MB (on chip) per CPU
Other Cache: N/A
Memory: 16 GB (8*512MB PC2700 DIMMS per 4cpu module)
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.3
Compiler: Intel(R) C++ Compiler for Linux 8.0 (Build 20031017)
MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 +FDO
C++ programs: -fast -ansi_alias +FDO
Extra Libraries: libsmartheap64.a

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.