



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Superdome (1000MHz PA-8800, 16 cells)

SPECint_rate2000 = 541
SPECint_rate_base2000 = 518

SPEC license #: 3 Tested by: HP Richardson Test date: Jan-2004 Hardware Avail: Mar-2004 Software Avail: Feb-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	64	233	446	64	227	457
175.vpr	64	199	522	64	199	522
176.gcc	64	118	691	64	118	691
181.mcf	64	330	404	64	330	404
186.crafty	64	113	658	64	113	658
197.parser	64	299	446	64	287	466
252.eon	64	180	536	64	159	605
253.perlbnk	64	274	489	64	237	564
254.gap	64	340	240	64	335	244
255.vortex	64	133	1058	64	126	1116
256.bzip2	64	240	463	64	217	514
300.twolf	64	354	630	64	347	641

Hardware	Software
CPU: PA-8800	Operating System: HPUNIX11i-TCOE B.11.11.0312
CPU MHz: 1000	Compiler: HP aC++ Compiler A.03.52
FPU: Integrated	HP C/ANSIC B.11.11.08
CPU(s) enabled: 64 cores, 32 chips, 2 cores/chip	File System: OnLineJFS
CPU(s) orderable: 4-128 cores (up to 64/partition)	System State: Multi-user
Parallel: no	
Primary Cache: 0.75MBI + 0.75MBD (on chip) per core	
Secondary Cache: 32MB (off chip) shared by 2 cores	
L3 Cache: N/A	
Other Cache: N/A	
Memory: 256GB (512 * 512MB DIMMs)	
Disk Subsystem: 10x36GB 10K rpm SCSI (striped)	
Other Hardware: N/A	

Notes/Tuning Information

Portability flags:

```

176.gcc: -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DHP
252.eon: -DFMAX_IS_DOUBLE
253.perlbnk: -DSPEC_CPU2000_HP
254.gap: -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
        -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

```

Baseline compile flags:

```

C      : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive
C++    : +I/+P +Oall +Ostatic_prediction -Wl,-a,archive

```

Peak compile flags:

```

164.gzip: +I/+P +Oall +Optrs_strongly_typed +Oinline_budget=800
        -Wl,-a,archive +Ostatic_prediction
175.vpr: basepeak=true
176.gcc: basepeak=true
181.mcf: basepeak=true
186.crafty: basepeak=true

```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Superdome (1000MHz PA-8800, 16 cells)

SPECint_rate2000 = 541
SPECint_rate_base2000 = 518

SPEC license #: 3 | Tested by: HP Richardson | Test date: Jan-2004 | Hardware Avail: Mar-2004 | Software Avail: Feb-2004

Notes/Tuning Information (Continued)

```

197.parser: +I/+P +Oall +Odataprefetch +ESficc +Oinline_budget=400
            +Owhole_program_mode -Wl,-a,archive +Ostatic_prediction
252.eon:    +I/+P +noeh +O4 +Optrs_strongly_typed +Olibcalls +Oentrysched
            +A +ESficc -Wl,-a,archive +Ostatic_prediction
253.perlbnk: +I/+P +Oall +ESlit +ESficc +Optrs_strongly_typed
            +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
            linked with /opt/langtools/lib/fastmem.o
254.gap:    +I/+P +Oall +ESlit +ESficc +Optrs_strongly_typed
            +Opromote_indirect_calls -Wl,-a,archive +Ostatic_prediction
255.vortex: +I/+P +Oall +Oinline_budget=800 +Optrs_strongly_typed
            -Wl,-a,archive +Ostatic_prediction
256.bzip2:  +I/+P +Oall +Odataprefetch +Optrs_strongly_typed +Owhole_program_mode
            +Onoptrs_to_globals +Oinline_budget=80 -Wl,-a,archive +Ostatic_prediction
300.twolf:  +I/+P +Oall +Optrs_strongly_typed -Wl,-a,archive +Ostatic_prediction

```

Kernel Tunables:

```

dbc_max_pct=20
dbc_min_pct=20
maxdsiz=3221225472
maxssiz=401604608
maxdsiz_64bit=4396972761584
maxssiz_64bit=1073741824
vps_pagesize=4096
vps_ceiling=16384

```

Other notes:

The system under test had the HP-UX 11i v1 December 2003 Technical Computing Operating Environment (version 11.11.0312) and DART63 (December 2003) compilers installed, with the following patches applied:

```

GOLDAPPS11i Gold Applications Patches for HP-UX 11i v1, December 2003
GOLDBASE11i Gold Base Patches for HP-UX 11i v1, December 2003
HWEnable11i Hardware Enablement Patches for HP-UX 11i v1, December 2003
HWTEST1111 Hardware Enablement Patches for PA-8800 (prerelease)
PHSS_29483 aC++ compiler cumulative patch (A.03.52)
PHSS_30002 Fortran90 cumulative patch (B.11.01.74)

```

System was configured with all memory interleaved

System configured as a single partition with 16 cells and 2 PA-8800 modules (each with 2 processors) per cell

Filesystem used for spec runs mounted "tmplog"