



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V890(8 processor)

SPECfp\_rate2000 = 161  
SPECfp\_rate\_base2000 = 137

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2004 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	229	130	16	221	135
171.swim	16	875	65.8	16	192	300
172.mgrid	16	530	63.0	16	530	63.0
173.applu	16	314	124	16	259	151
177.mesa	16	179	145	16	163	159
178.galgel	16	164	328	16	124	433
179.art	16	33.4	1445	16	32.1	1505
183.quake	16	169	142	16	169	142
187.facerec	16	132	267	16	132	267
188.amp	16	361	113	16	363	112
189.lucas	16	598	62.0	16	598	62.0
191.fma3d	16	568	68.6	16	551	70.7
200.sixtrack	16	243	84.0	16	226	90.2
301.apsi	16	424	114	16	427	113

**Hardware**

CPU: UltraSPARC IV  
CPU MHz: 1350  
FPU: Integrated  
CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip  
CPU(s) orderable: 2,4,8 (order by # of chips)  
Parallel: No  
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)  
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)  
L3 Cache: None  
Other Cache: None  
Memory: 32GB 8-way interleaved  
Disk Subsystem: 1 x 73GB  
Other Hardware: None

**Software**

Operating System: Solaris 10  
Compiler: Sun Studio 9  
File System: ufs  
System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
CXX: CC  
F90: f90  
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6  
-Qoption iropt -Atile:skewp,-Ainline:cs=700  
(no feedback)



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V890(8 processor)

SPECfp\_rate2000 = 161  
SPECfp\_rate\_base2000 = 137

SPEC license #: 6 Tested by: Sun Microsystems Test date: Dec-2004 Hardware Avail: Feb-2005 Software Avail: Jan-2005

## Notes/Tuning Information (Continued)

```
172.mgrid: basepeak = yes
173.applu:  -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa:  -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art:   -fast -xipo=2 -xalias_level=std
           -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: basepeak= yes
187.facerec: basepeak= yes
188.ammp:   -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas:  basepeak =yes
191.fma3d:  -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
           -xprefetch=no
301.apsi:   -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```