




# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL35p (AMD Opteron (TM) 275)

SPECfp\_rate2000 = 33.4  
SPECfp\_rate\_base2000 = 30.8

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Jun-2005 Software Avail: Apr-2005



### Hardware

CPU: AMD Opteron (TM) 275  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB(I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 2x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x60GB ATA100 5400RPM  
 Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 1  
 SuSE kernel 2.6.5-7.139-smp  
 Compiler: PathScale EKO Compiler Suite, Release 2.1  
 AMD Core Math Library 2.5.1  
 File System: Linux/ext2  
 System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
               -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3 -TENV:X=4
               -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
               -INLINE:aggressive=on
  171.swim: -Ofast -LNO:fusion=2
  172.mgrid: -O3 -LNO:fusion=2:blocking=off
               -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
  173.applu: -Ofast -CG:local_fwd_sched=on
               -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
               -OPT:ro=3 -TENV:X=3 -WOPT:val=2
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL35p (AMD Opteron (TM) 275)

SPECfp\_rate2000 = 33.4  
SPECfp\_rate\_base2000 = 30.8

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Jun-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:    -Ofast -OPT:fast_complex RM_SOURCES=lapak.f90 +ACML
179.art:       -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake:     -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on -m32
187.facerec:   -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
               -LNO:fusion=2 -IPA:plimit=1500 +FDO
188.amp:       -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas:     -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -Ofast -CG:load_exe=1 +FDO
301.apsi:      -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Taskset utility used to bind process to CPU(s)