



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos G530 (3.8 GHz Intel Xeon)

SPECint2000 = 1771
SPECint_base2000 = 1768

SPEC license #: 97 Tested by: Acer Incorporated Test date: Sep-2005 Hardware Avail: Aug-2005 Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	111	1260	111	1260	[Bar chart showing ratio]			
175.vpr	1400	116	1209	115	1220	[Bar chart showing ratio]			
176.gcc	1100	52.2	2107	52.2	2107	[Bar chart showing ratio]			
181.mcf	1800	97.3	1851	97.3	1851	[Bar chart showing ratio]			
186.crafty	1000	71.2	1405	71.2	1405	[Bar chart showing ratio]			
197.parser	1800	118	1528	118	1528	[Bar chart showing ratio]			
252.eon	1300	54.8	2374	54.6	2381	[Bar chart showing ratio]			
253.perlbnk	1800	82.4	2184	82.3	2187	[Bar chart showing ratio]			
254.gap	1100	55.1	1998	55.1	1998	[Bar chart showing ratio]			
255.vortex	1900	65.7	2894	65.7	2894	[Bar chart showing ratio]			
256.bzip2	1500	115	1300	115	1305	[Bar chart showing ratio]			
300.twolf	3000	160	1877	160	1878	[Bar chart showing ratio]			

Hardware

CPU: Intel Xeon (3.8 GHz, 2MB L2, 800MHz system bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology Disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1024MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 146GB 10000RPM U320 SCSI HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ Compiler 8.1 Build 20041019Z for IA32
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos G530 (3.8 GHz Intel Xeon)

SPECint2000 =	1771
SPECint_base2000 =	1768

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Sep-2005 | Hardware Avail: Aug-2005 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at <http://www.acer.com>