



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 275

SPECint_rate2000 = 70.2
SPECint_rate_base2000 = 64.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Dec-2005 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	117	55.4	4	117	55.4
175.vpr	4	119	54.5	4	116	56.1
176.gcc	4	68.5	74.5	4	68.7	74.3
181.mcf	4	212	39.5	4	170	49.2
186.crafty	4	70.1	66.2	4	63.8	72.8
197.parser	4	133	63.0	4	133	63.0
252.eon	4	77.1	78.3	4	54.9	110
253.perlbnk	4	125	66.7	4	115	72.7
254.gap	4	74.4	68.6	4	74.4	68.6
255.vortex	4	85.3	103	4	77.3	114
256.bzip2	4	132	52.9	4	129	54.1
300.twolf	4	203	68.7	4	171	81.5

Hardware

CPU: AMD Opteron (TM) 275 processor (2.20 GHz)
CPU MHz: 2200
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 64KBI + 64KBD on chip, per core
Secondary Cache: 1024KB (I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x2048MB DDR-RAM PC3200R
Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ 8.0
Build 20040318Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
for C++ programs: -fast -GX -GR +FDO

Peak tuning flags

164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
181.mcf: -fast -QaxN +FDO shlw32M.lib
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 275

SPECint_rate2000 = 70.2
SPECint_rate_base2000 = 64.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Dec-2005 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

boot options: /NoExecute=alwaysoff
/USEPMTIMER

BIOS settings: Memory timing=1T

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>