



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM BladeCenter JS21 (2700 MHz, 1 CPU)

SPECfp2000 = 2259  
SPECfp\_base2000 = 2060

SPEC license #: 11 | Tested by: IBM | Test date: Jan-2006 | Hardware Avail: Mar-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	70.5	2270	64.6	2479
171.swim	3100	127	2445	123	2517
172.mgrid	1800	110	1635	79.3	2270
173.applu	2100	163	1286	137	1528
177.mesa	1400	83.6	1675	76.8	1823
178.galgel	2900	93.2	3110	82.8	3504
179.art	2600	33.1	7859	31.8	8175
183.earthquake	1300	35.4	3671	34.7	3746
187.facerec	1900	73.3	2592	71.5	2656
188.amp	2200	220	1002	182	1212
189.lucas	2000	104	1924	92.8	2154
191.fma3d	2100	129	1627	121	1732
200.sixtrack	1100	101	1089	97.6	1127
301.apsi	2600	162	1600	165	1574

### Hardware

CPU: IBM PowerPC 970MP  
 CPU MHz: 2700  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 2 chips, 1 core/chip  
 CPU(s) orderable: 2  
 Parallel: No  
 Primary Cache: 64KBI+32KBD (on chip)/core  
 Secondary Cache: 1MB unified (on chip)/core  
 L3 Cache: None  
 Other Cache: None  
 Memory: 4x2GB PC2-4200 533MHz ECC Chipkill DDR2  
 Disk Subsystem: 2x 73GB 10,000 rpm 2.5" SFF Serial Attached SCSI  
 Other Hardware: BladeCenter H

### Software

Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 XL Fortran Enterprise Edition Version 10.1 for AIX  
 Other Software: ESSL 4.2.0.4  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

### Portability Flags:

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,  
 178.galgel, 200.sixtrack, 301.apsi  
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

### Base Optimization Flags:

Fortran: -O5 -lhmu -blpdata -lmass  
 C: -qpdf1/pdf2  
 -O5 -blpdata -qalign=natural

### Peak Optimization Flags

168.wupwise: -O5 -qsave -blpdata -lhmu -qenablevmx -lmass  
 171.swim: -qpdf1/pdf2  
 -O4 -qfdpr -blpdata  
 fdpr -q -O3  
 172.mgrid: -qpdf1/pdf2  
 -O4 -q64 -blpdata



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM BladeCenter JS21 (2700 MHz, 1 CPU)

SPECfp2000 = 2259  
SPECfp\_base2000 = 2060

SPEC license #: 11 | Tested by: IBM | Test date: Jan-2006 | Hardware Avail: Mar-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```

173.applu: -O5 -qarch=pwr3 -qtune=pwr3 -qalign=struct=natural -qfdpr -q64 -blpdata
           fdpr -q -O3
177.mesa:  -qpdf1/pdf2
           -O5 -qfdpr
           fdpr -q -O3
178.galgel: -qpdf1/pdf2
           -O5 -qfdpr -qalign=struct=natural -q64 -blpdata -qenablevmx -lmass -qessl -lessl
           fdpr -q -O3
179.art:   -O5 -blpdata -lhmu
183.equake: -qpdf1/pdf2
           -O3 -qarch=auto -qtune=auto -qipa=level=2 -blpdata
187.facerec: -O5 -qfdpr -blpdata -qenablevmx -lmass -qessl -lessl
           fdpr -q -O3
188.ammp:  -O5 -qalign=natural -blpdata -lhmu -qenablevmx -lmass
189.lucas: -O3 -qarch=auto -qtune=auto -qfdpr -blpdata
           fdpr -q -O3
191.fma3d: -O5 -qarch=pwr3 -qtune=pwr3 -qalign=struct=natural -qfdpr -blpdata
           fdpr -q -O3
200.sixtrack: -O3 -qarch=auto -qtune=auto -qfdpr -q64 -qenablevmx -lmass
           fdpr -q -O3
301.apsi:  -O5 -qhot=arraypad -Q -qalign=struct=natural -q64 -qenablevmx -lmass

```

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-04 Recommended Technology Level.

ESSL: Engineering and Scientific Subroutine Library

```

ANSI C89:      IBM XL C for AIX invoked as xlc
Fortran 77:    IBM XL Fortran for AIX invoked as xlf90
Fortran 90:    IBM XL Fortran for AIX invoked as xlf90

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=100 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \$$ \$$ $SPECUSERNUM; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

One core was deconfigured at the open-firmware prompt, using the command

```
boot -s cpu=1
```