



# SPEC<sup>®</sup> CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Rh-1  
(Intel Xeon processor X5450)

SPECint<sup>®</sup>\_rate2006 = 130

SPECint\_rate\_base2006 = 104

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2007

Hardware Availability: Dec-2007

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5450  
 CPU Characteristics: 3.00 GHz, 2x6 MB L2 shared, 1333 MHz bus  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
 Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l\_cc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ext2  
 System State: Multiuser, Runlevel 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap library 8.1 binutils-2.17.tar.gz, Version 2.17



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Rh-1  
(Intel Xeon processor X5450)

SPECint\_rate2006 = 130

SPECint\_rate\_base2006 = 104

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2007

Hardware Availability: Dec-2007

Software Availability: Nov-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	528	148	530	147	<u>529</u>	<u>148</u>	8	439	178	436	179	<u>437</u>	<u>179</u>
401.bzip2	8	<u>731</u>	<u>106</u>	736	105	726	106	8	690	112	695	111	<u>692</u>	<u>112</u>
403.gcc	8	755	85.3	<u>750</u>	<u>85.9</u>	749	86.0	8	<u>749</u>	<u>86.0</u>	752	85.7	748	86.1
429.mcf	8	929	78.5	<u>924</u>	<u>78.9</u>	923	79.1	8	938	77.8	<u>932</u>	<u>78.3</u>	931	78.4
445.gobmk	8	564	149	555	151	<u>563</u>	<u>149</u>	8	<u>517</u>	<u>162</u>	508	165	518	162
456.hmmer	8	594	126	<u>594</u>	<u>126</u>	593	126	8	<u>350</u>	<u>213</u>	351	213	349	214
458.sjeng	8	<u>694</u>	<u>139</u>	691	140	695	139	8	632	153	631	153	<u>631</u>	<u>153</u>
462.libquantum	8	3620	45.8	<u>3384</u>	<u>49.0</u>	3300	50.2	1	<u>89.6</u>	<u>231</u>	90.8	228	89.4	232
464.h264ref	8	704	251	<u>703</u>	<u>252</u>	703	252	8	<u>681</u>	<u>260</u>	674	263	682	260
471.omnetpp	8	961	52.1	957	52.2	<u>958</u>	<u>52.2</u>	8	944	53.0	<u>943</u>	<u>53.0</u>	943	53.0
473.astar	8	749	75.0	740	75.9	<u>741</u>	<u>75.8</u>	8	693	81.0	<u>697</u>	<u>80.6</u>	698	80.5
483.xalancbmk	8	454	122	<u>452</u>	<u>122</u>	450	123	8	454	122	<u>452</u>	<u>122</u>	450	123

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores (default).

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled

## General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2, 456.hmmer, for peak, are compiled in 64-bit mode

The NEC Express5800/120Rh-1(Intel Xeon Processor X5450), the NEC Express5800/120Rj-2(Intel Xeon Processor X5450), the Bull NovaScale R440 E1 (Intel Xeon X5450,3.00GHz) and the Bull NovaScale R460 E1 (Intel Xeon X5450,3.00GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon Processor X5450) model.

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Rh-1  
(Intel Xeon processor X5450)

**SPECint\_rate2006 = 130**

**SPECint\_rate\_base2006 = 104**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Dec-2007

**Hardware Availability:** Dec-2007

**Software Availability:** Nov-2007

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/opt/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:  
icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Rh-1  
(Intel Xeon processor X5450)

**SPECint\_rate2006 = 130**

**SPECint\_rate\_base2006 = 104**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Dec-2007

**Hardware Availability:** Dec-2007

**Software Availability:** Nov-2007

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
403.gcc: -fast -inline-calloc -opt-malloc-options=3  
429.mcf: -fast -prefetch  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias  
456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs -L/opt/SmartHeap\_8.1/lib -lsmarheap  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs -L/opt/SmartHeap\_8.1/lib -lsmarheap  
483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Rh-1  
(Intel Xeon processor X5450)

**SPECint\_rate2006 = 130**

**SPECint\_rate\_base2006 = 104**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Dec-2007

**Hardware Availability:** Dec-2007

**Software Availability:** Nov-2007

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-ia32-intel64-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-ia32-intel64-linux-flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 16:13:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 January 2008.