



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint®2006 = 25.3

IBM System x3650 (Intel Xeon E5440)

SPECint_base2006 = 22.0

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jan-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon E5440
CPU Characteristics:	1333MHz system bus
CPU MHz:	2826
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2 GB DDR2-5300F ECC)
Disk Subsystem:	1 x 36 GB SAS, 15000 RPM
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 10 (x86_64), kernel 2.6.16.21-0.8-smp
Compiler:	Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Multi-user, run level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 25.3

IBM System x3650 (Intel Xeon E5440)

SPECint_base2006 = 22.0

CPU2006 license: 11

Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	531	18.4	532	18.4	536	18.2	426	23.0	424	23.1	424	23.1
401.bzip2	628	15.4	628	15.4	627	15.4	580	16.6	581	16.6	582	16.6
403.gcc	573	14.1	574	14.0	573	14.0	425	18.9	425	18.9	424	19.0
429.mcf	427	21.4	426	21.4	425	21.5	392	23.3	393	23.2	393	23.2
445.gobmk	565	18.6	565	18.6	564	18.6	509	20.6	509	20.6	509	20.6
456.hmmer	628	14.8	629	14.8	628	14.8	362	25.8	362	25.8	361	25.8
458.sjeng	716	16.9	721	16.8	719	16.8	647	18.7	647	18.7	644	18.8
462.libquantum	97.5	212	101	204	95.6	217	97.9	212	98.0	211	98.2	211
464.h264ref	755	29.3	742	29.8	756	29.3	704	31.4	703	31.5	704	31.4
471.omnetpp	421	14.9	423	14.8	420	14.9	384	16.3	382	16.4	383	16.3
473.astar	491	14.3	497	14.1	495	14.2	446	15.7	450	15.6	446	15.7
483.xalancbmk	281	24.5	282	24.5	281	24.5	281	24.5	282	24.5	281	24.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer, for peak, are compiled in 64-bit mode

Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Enabled

OMP_NUM_THREADS set to number of cores

KMP_AFFINITY set to physical,0

KMP_STACKSIZE set to null

Powersaved dameon was disabled in OS

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 25.3

IBM System x3650 (Intel Xeon E5440)

SPECint_base2006 = 22.0

CPU2006 license: 11

Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

```
-fast -vec-guard-write -parallel -par-runtime-control
```

C++ benchmarks:

```
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc
```

```
401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include
```

```
456.hmmr: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include
```

C++ benchmarks:

```
icpc
```

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32
```

```
401.bzip2: -DSPEC_CPU_LP64
```

```
456.hmmr: -DSPEC_CPU_LP64
```

```
462.libquantum: -DSPEC_CPU_LINUX
```

```
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation	SPECint2006 =	25.3
IBM System x3650 (Intel Xeon E5440)	SPECint_base2006 =	22.0
CPU2006 license: 11	Test date:	Jan-2008
Test sponsor: IBM Corporation	Hardware Availability:	Jan-2008
Tested by: IBM Corporation	Software Availability:	Nov-2007

Peak Optimization Flags (Continued)

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
               -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
            -auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
            -no-prec-div -ansi-alias

456.hmmmer: -fast -unroll12 -ansi-alias -opt-multi-version-aggressive
             -auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll14 -O0 -prefetch
                -opt-streaming-stores always -vec-guard-write
                -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
              -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
              -no-prec-div -ansi-alias -opt-ra-region-strategy=block
              -Wl,-z,muldefs
              -L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
            -no-prec-div -ansi-alias -opt-ra-region-strategy=routine
            -Wl,-z,muldefs
            -L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes
```

Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint2006 = 25.3

IBM System x3650 (Intel Xeon E5440)

SPECint_base2006 = 22.0

CPU2006 license: 11

Test date: Jan-2008

Test sponsor: IBM Corporation

Hardware Availability: Jan-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.20.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.20.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 15:51:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 February 2008.