



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp<sup>®</sup>\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5260  
 CPU Characteristics: 3.33 GHz, 6 MB L2, 1333 MHz bus  
 CPU MHz: 3333  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smpp  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l\_cc\_p\_10.1.008, l\_fc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.tar.gz, Version 2.17

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1515	35.9	<u>1529</u>	<u>35.6</u>	1531	35.5	4	<u>1499</u>	<u>36.3</u>	1501	36.2	1488	36.5
416.gamess	4	801	97.7	801	97.8	<u>801</u>	<u>97.7</u>	4	<u>790</u>	<u>99.1</u>	789	99.2	791	99.0
433.milc	4	1590	23.1	<u>1588</u>	<u>23.1</u>	1585	23.2	4	1586	23.1	<u>1581</u>	<u>23.2</u>	1553	23.6
434.zeusmp	4	696	52.3	690	52.8	<u>693</u>	<u>52.6</u>	4	<u>672</u>	<u>54.1</u>	680	53.5	671	54.3
435.gromacs	4	<u>339</u>	<u>84.3</u>	340	84.0	338	84.4	4	<u>335</u>	<u>85.3</u>	335	85.3	337	84.7
436.cactusADM	4	918	52.1	<u>919</u>	<u>52.0</u>	923	51.8	1	<u>186</u>	<u>64.2</u>	187	64.0	186	64.4
437.leslie3d	4	1423	26.4	1442	26.1	<u>1441</u>	<u>26.1</u>	4	<u>1353</u>	<u>27.8</u>	1356	27.7	1346	27.9
444.namd	4	460	69.8	456	70.3	<u>457</u>	<u>70.2</u>	4	<u>454</u>	<u>70.7</u>	453	70.8	454	70.6
447.dealII	4	493	92.8	<u>494</u>	<u>92.7</u>	497	92.1	4	<u>471</u>	<u>97.2</u>	471	97.1	470	97.4
450.soplex	4	<u>1096</u>	<u>30.4</u>	1109	30.1	1095	30.5	4	988	33.8	<u>982</u>	<u>34.0</u>	981	34.0
453.povray	4	<u>190</u>	<u>112</u>	190	112	190	112	4	165	129	162	131	<u>165</u>	<u>129</u>
454.calculix	4	484	68.2	<u>483</u>	<u>68.4</u>	478	69.1	4	343	96.2	<u>341</u>	<u>96.9</u>	338	97.6
459.GemsFDTD	4	1645	25.8	1681	25.3	<u>1678</u>	<u>25.3</u>	4	1590	26.7	<u>1590</u>	<u>26.7</u>	1588	26.7
465.tonto	4	520	75.7	<u>518</u>	<u>76.0</u>	515	76.4	4	508	77.5	495	79.5	<u>507</u>	<u>77.7</u>
470.lbm	4	<u>3198</u>	<u>17.2</u>	3188	17.2	3209	17.1	2	798	34.4	<u>781</u>	<u>35.2</u>	771	35.6
481.wrf	4	<u>867</u>	<u>51.5</u>	868	51.5	865	51.6	4	865	51.7	<u>866</u>	<u>51.6</u>	866	51.6
482.sphinx3	4	1644	47.4	1611	48.4	<u>1611</u>	<u>48.4</u>	2	<u>664</u>	<u>58.7</u>	668	58.4	663	58.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs  
OMP\_NUM\_THREADS set to number of cores

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

## General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

The NEC Express5800/120Lj(Intel Xeon X5260) and the Bull NovaScale T860 E1(Intel Xeon X5260,3.33GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/120Lj(Intel Xeon X5260) model.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

## Base Optimization Flags (Continued)

C++ benchmarks:  
-fast

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
-fast

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

## Peak Portability Flags (Continued)

465.tonto: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

### C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32  
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3  
482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32  
447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-  
450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3  
453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch  
416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-  
434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast  
437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3  
459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch  
465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale T860 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp\_rate2006 = 55.5

SPECfp\_rate\_base2006 = 49.3

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Feb-2008  
**Software Availability:** Nov-2007

## Peak Optimization Flags (Continued)

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 15:30:09 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 March 2008.