



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Itaotec

### SPECfp®\_rate2006 = 42.3

### Servidor Itaotec MX221 (Intel Xeon E5440)

### SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001


Test sponsor: Itaotec

Tested by: Itaotec

Test date: Apr-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008



#### Hardware

CPU Name: Intel Xeon E5440  
 CPU Characteristics:  
 CPU MHz: 2830  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

#### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ and Fortran Compiler for Linux version 10.1  
 Build 20080112 Package ID: l\_cc\_p\_10.1.012, l\_fc\_p\_10.1.012  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run Level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp\_rate2006 = 42.3

Servidor Itaotec MX221 (Intel Xeon E5440)

SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Apr-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8 \* 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)  
Disk Subsystem: 1 x SCSI, 73GB, 15000 RPM  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: Binutils 2.17.10.50

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2329	23.3	<u>2331</u>	<u>23.3</u>	2332	23.3	4	2329	23.3	<u>2331</u>	<u>23.3</u>	2332	23.3
416.gamess	4	<u>944</u>	<u>83.0</u>	944	83.0	946	82.8	4	924	84.8	928	84.4	<u>924</u>	<u>84.7</u>
433.milc	4	1723	21.3	1712	21.5	<u>1722</u>	<u>21.3</u>	4	1715	21.4	1711	21.5	<u>1715</u>	<u>21.4</u>
434.zeusmp	4	839	43.4	840	43.3	<u>839</u>	<u>43.4</u>	4	<u>839</u>	<u>43.4</u>	811	44.9	840	43.3
435.gromacs	4	<u>400</u>	<u>71.3</u>	400	71.3	400	71.3	4	<u>396</u>	<u>72.2</u>	396	72.1	395	72.3
436.cactusADM	4	936	51.1	941	50.8	<u>939</u>	<u>50.9</u>	1	182	65.8	<u>180</u>	<u>66.4</u>	179	66.8
437.leslie3d	4	2209	17.0	2217	17.0	<u>2215</u>	<u>17.0</u>	2	<u>1095</u>	<u>17.2</u>	1096	17.2	1095	17.2
444.namd	4	<u>537</u>	<u>59.8</u>	537	59.7	537	59.8	4	533	60.2	<u>533</u>	<u>60.2</u>	533	60.2
447.dealII	4	617	74.2	593	77.2	<u>596</u>	<u>76.8</u>	4	566	80.9	<u>567</u>	<u>80.7</u>	589	77.8
450.soplex	4	1431	23.3	1421	23.5	<u>1426</u>	<u>23.4</u>	4	1131	29.5	<u>1131</u>	<u>29.5</u>	1130	29.5
453.povray	4	<u>226</u>	<u>94.1</u>	225	94.5	229	93.1	4	188	113	<u>188</u>	<u>113</u>	188	113
454.calculix	4	573	57.6	560	58.9	<u>571</u>	<u>57.8</u>	4	405	81.4	400	82.5	<u>401</u>	<u>82.3</u>
459.GemsFDTD	4	2411	17.6	2405	17.6	<u>2408</u>	<u>17.6</u>	4	2398	17.7	<u>2400</u>	<u>17.7</u>	2401	17.7
465.tonto	4	620	63.5	616	63.8	<u>620</u>	<u>63.5</u>	4	604	65.2	606	64.9	<u>606</u>	<u>64.9</u>
470.lbm	4	2996	18.3	<u>2995</u>	<u>18.4</u>	2994	18.4	4	2996	18.3	<u>2995</u>	<u>18.4</u>	2994	18.4
481.wrf	4	1413	31.6	1412	31.7	<u>1413</u>	<u>31.6</u>	4	<u>1413</u>	<u>31.6</u>	1418	31.5	1409	31.7
482.sphinx3	4	<u>2312</u>	<u>33.7</u>	2299	33.9	2329	33.5	4	<u>2312</u>	<u>33.7</u>	2299	33.9	2329	33.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_STACK\_SIZE set to 64M  
KMP\_AFFINITY set to physical,0

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
'/usr/bin/taskset' used to bind benchmark copies to processors, except for 436.cactusADM at peak.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp\_rate2006 = 42.3

Servidor Itaotec MX221 (Intel Xeon E5440)

SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Apr-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Platform Notes

BIOS configuration:  
Hardware Prefetch Enabled

## General Notes

This result was measured on the Servidor Itaotec MX201.  
The Servidor Itaotec MX221 and the Servidor Itaotec MX201 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp\_rate2006 = 42.3

Servidor Itaotec MX221 (Intel Xeon E5440)

SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Apr-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-fast

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
-fast

## Peak Compiler Invocation

C benchmarks:  
icc

C++ benchmarks (except as noted below):  
icpc

450.soplex: /opt/intel/cc/10.1.012/bin/icpc -L/opt/intel/cc/10.1.012/lib  
-I/opt/intel/cc/10.1.012/include

Fortran benchmarks (except as noted below):  
ifort

437.leslie3d: /opt/intel/fc/10.1.012/bin/ifort -L/opt/intel/fc/10.1.012/lib  
-I/opt/intel/fc/10.1.012/include

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECfp\_rate2006 = 42.3

Servidor Itaotec MX221 (Intel Xeon E5440)

SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: Apr-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Peak Portability Flags (Continued)

465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Peak Optimization Flags

### C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp\_rate2006 = 42.3

Servidor Itautec MX221 (Intel Xeon E5440)

SPECfp\_rate\_base2006 = 39.5

CPU2006 license: 9001

Test sponsor: Itautec

Tested by: Itautec

Test date: Apr-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-FP-intel64-linux-flags.20090713.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.  
Report generated on Tue Jul 22 17:22:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 13 May 2008.