



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint®2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13


Test date: Sep-2012

Test sponsor: Intel Corporation

Hardware Availability: Sep-2012

Tested by: Intel Corporation

Software Availability: Apr-2011



Hardware

CPU Name: Intel Core i3-3240
 CPU Characteristics:
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 3 MB I+D on chip per chip
 Other Cache: None
 Memory: 8 GB (2 x 4 GB 2Rx8 PC3-12800U-9)
 Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows;
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2012

Hardware Availability: Sep-2012

Software Availability: Apr-2011

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	365	26.8	365	26.8	364	26.8	<u>279</u>	<u>35.0</u>	279	35.0	280	34.9
401.bzip2	453	21.3	440	22.0	439	22.0	<u>426</u>	<u>22.7</u>	426	22.7	425	22.7
403.gcc	<u>299</u>	<u>26.9</u>	299	26.9	299	26.9	283	28.4	283	28.4	283	28.4
429.mcf	154	59.1	155	58.7	154	59.2	<u>154</u>	<u>59.1</u>	155	58.7	154	59.2
445.gobmk	410	25.6	410	25.6	410	25.6	387	27.1	386	27.2	386	27.2
456.hammer	164	56.9	164	57.0	164	57.0	164	56.9	164	57.0	164	57.0
458.sjeng	452	26.8	453	26.7	453	26.7	452	26.8	453	26.7	453	26.7
462.libquantum	39.4	526	39.3	527	39.3	527	39.4	526	39.3	527	39.3	527
464.h264ref	375	59.0	375	59.1	375	59.0	354	62.6	353	62.7	354	62.6
471.omnetpp	289	21.6	288	21.7	289	21.7	273	22.9	274	22.8	274	22.9
473.astar	272	25.8	273	25.7	272	25.8	272	25.8	273	25.7	272	25.8
483.xalancbmk	192	35.9	191	36.1	191	36.1	192	35.9	191	36.1	191	36.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

ipsxe-comp-vars batch file invoked with intel64

Platform Notes

Sysinfo program C:\CPU200~1.17A\Docs\sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on CltE840F2070731 Wed Sep 19 13:13:24 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Ultimate
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model   : DH77KC__
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3400 Mhz
BIOS Version  : Intel Corp. KCH7710H.86A.0095.2012.0608.1754, 6/8/2012
Total Physical Memory: 8,092 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
L2CacheSize  : 512
L3CacheSize  : 3072
MaxClockSpeed : 3400
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2012

Hardware Availability: Sep-2012

Software Availability: Apr-2011

Platform Notes (Continued)

Name : Intel(R) Core(TM) i3-3240 CPU @ 3.40GHz

NumberOfCores : 2

NumberOfLogicalProcessors: 4

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores

KMP_AFFINITY set to granularity=fine,scatter

Binaries compiled on a system with 1x Intel Core i7-860 CPU

+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Base Portability Flags

400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
-DSPEC_CPU_NO_NEED_VA_COPY

401.bzip2: -DSPEC_CPU_P64

403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64

429.mcf: -DSPEC_CPU_P64

445.gobmk: -DSPEC_CPU_P64

456.hmmer: -DSPEC_CPU_P64

458.sjeng: -DSPEC_CPU_P64

462.libquantum: -DSPEC_CPU_P64

464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES

471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64

473.astar: -DSPEC_CPU_P64

483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13

Test date: Sep-2012

Test sponsor: Intel Corporation

Hardware Availability: Sep-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Base Optimization Flags

C benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32 /F512000000

C++ benchmarks:

-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE

401.bzip2: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32 /F512000000

403.gcc: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qauto-ilp32 /F512000000

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13

Test date: Sep-2012

Test sponsor: Intel Corporation

Hardware Availability: Sep-2012

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32
/F512000000

C++ benchmarks:

471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qansi-alias
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000
shlw64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 42.9

Intel DH77KC Motherboard (Intel Core i3-3240)

SPECint_base2006 = 41.1

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2012

Hardware Availability: Sep-2012

Software Availability: Apr-2011

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 13:17:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 November 2012.