



# SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~SPECint\_rate2006 = NC~~

~~SPECint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

	Copies
400.perlbench	
401.bzip2	
403.gcc	
429.mcf	
445.gobmk	
456.hmmer	
458.sjeng	
462.libquantum	
464.h264ref	
471.omnetpp	
473.astar	
483	

	Hardware	Software
CPU Name:	Intel Xeon E5-2637 v3	Operating System: Red Hat Enterprise Linux Server release 7.0 (Maipo)
CPU Characteristics:	Intel Turbo Boost Technology up to 3.70 GHz	Compiler: Kernel 3.10.0-123.el7.x86_64
CPU MHz:	3500	C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux
FPU:	Integrated	Auto Parallel: No
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip, 2 threads/core	File System: xfs
CPU(s) orderable:	1,2 chips	System State: Run level 3 (multi-user)
Primary Cache:	32 KB I + 32 KB D on chip per core	

*Continued on next page*



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~SPECint\_rate2006 = NC~~

~~SPECint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

Secondary Cache:	256 KB I+D on chip per core	Base Pointers:	32-bit
L3 Cache:	15 MB I+D on chip per chip	Link Pointers:	32/64-bit
Other Cache:	None	Other Software:	Microquill SmartHeap V10.0
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)		
Disk Subsystem:	2 x 400 GB SSD SAS, RAID 1		
Other Hardware:	None		

**Results Table**

Benchmark	Baseline						Peak					
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
401.bzip2	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
403.gcc	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
429.mcf	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
445.gobmk	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
456.hmmer	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
458.sjeng	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
462.libquantum	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
464.h264ref	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
471.omnetpp	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
473.astar	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC
483.xalancbmk	16	NC	NC	NC	NC	NC	NC	16	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

### Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Transparent Huge Pages enabled with:

```
echo always > /sys/kernel/mm/transparent_hugepage/enabled
```

Filesystem page cache cleared with:

```
echo 1> /proc/sys/vm/drop_caches
```

runspec command invoked through numactl, i.e.:

```
numactl --interleave=all runspec <etc>
```

### Platform Notes

BIOS Configuration:

HP Power Profile set to Custom

HP Power Regulator to HP Static High Performance Mode

Minimum Processor Idle Power Core State set to C6 State

Minimum Processor Idle Power Package State set to No Package State

QPI Snoop Configuration set to Early Snoop

Thermal Configuration set to Maximum Cooling

Collaborative Power Control set to Disabled

Processor Power and Utilization Monitoring set to Disabled

Memory Double Refresh Rate set to 1x Refresh

Sysinfo program /cpu2006/config/sysinfo.rev6914

\$Rev: 6.14 \$Date: 2014-06-25 #\$ e3fbb8667b5a285932ceab81e28219e1

running on W-bl460c\_gen9-VP2.1 Wed Nov 19 11:21:29 2014

~~This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:~~

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2637 v3 @ 3.50GHz

2 "physical id"s (chips)

16 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 4

siblings : 8

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

### Platform Notes (Continued)

```
physical 0: cores 0 1 4 5
physical 1: cores 0 1 4 5
cache size : 15360 KB

From /proc/meminfo
MemTotal:      263846220 kB
HugePages_Total:
Hugepagesize:    2048 kB

From /etc/*release* /etc/*version*
os-release:
  NAME="Red Hat Enterprise Linux Server"
  VERSION="7.0 (Maipo)"
  ID="rhel"
  ID_LIKE="fedora"
  VERSION_ID="7.0"
  PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
  ANSI_COLOR="31"
  CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a
Linux Wbl460c_gen9-VP2.1 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57 EDT
2014 x86_64 x86_64 GNU/Linux

run-level 3 Nov 19 11:14

SPEC is set to: /cpu2006
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda4        xfs   277G  7.7G  270G  3% /
Additional information from dmidecode:
```

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Platform Notes (Continued)

BIOS HP I36 08/26/2014

Memory:

16x HP NOT AVAILABLE 16 GB 2 rank 2133 Mhz

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/cpu2006/lib/32:/cpu2006/libs/64:/cpu2006/sh"

Binaries compiled on a system with 1x Core i5-4670K CPU + 16GB  
memory using RedHat EL 7.0

## Base Compiler Invocation

C benchmarks:

icc -m32 -I /opt/intel/composer\_xe\_2015/lib/ia32

C++ benchmarks:

i\_c -m32 -L /opt/intel/composer\_xe\_2015/lib/ia32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.mq quantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-opt-mem-layout-trans=3

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

Hewlett-Packard Company Proliant BL460c Gen9 (3.50 GHz, Intel Xeon E5-2637 v3)	<b>SPECint_rate2006 =</b> NC <b>SPECint_rate_base2006 =</b> NC
<b>CPU2006 license:</b> 3 <b>Test sponsor:</b> Hewlett-Packard Company <b>Tested by:</b> Hewlett-Packard Company	<b>Test date:</b> Nov-2014 <b>Hardware Availability:</b> Sep-2014 <b>Software Availability:</b> Sep-2014

SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.

## ~~Base Optimization Flags (Continued)~~

## C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prune-div -opt-prune-fetch  
-opt-mem-layout-trans=3 -m1,-z,mul,efs -L/sh -lsmartheap
```

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

# Peak Compiler Invocation

C benchmarks (except as noted below):

~~icc -m32 -L/opt/intel/composer\_xe\_2015/lib/ia32~~

40 oberbenc icc -m 4

~~401.zip2: 100 -m64~~

icc -m64

458 sieng·icc ·m64

~~Charles:~~

## ~~C++ benchmarks:~~

```
icpc -m32 -L/opt/intel/composer_xe_2015/lib/ia32
```



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_LP64  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmr: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32  
401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-O2 -prefetch -auto-ilp32 -ansi-alias  
403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div  
429.mcf: basepeak = yes  
453.xalancbmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3  
456.hmmr: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32  
458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32  
462.libquantum: basepeak = yes

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~Specint\_rate2006 = NC~~

~~Specint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

## Peak Optimization Flags (Continued)

464.h264ref: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartr

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc -Dalloca\_a=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revE.xml>



# SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

Proliant BL460c Gen9  
(3.50 GHz, Intel Xeon E5-2637 v3)

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

~~SPECint\_rate2006 = 10~~

~~SPECint\_rate\_base2006 = NC~~

Test date: Nov-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2014

**SPEC has determined that this result is not in compliance with the SPEC OSG Guidelines for General Availability and the SPEC CPU2006 run and reporting rules. Specifically, the submitter has notified SPEC that the system was run with a memory configuration that is not supported by Hewlett-Packard with the given processor configuration.**

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Nov 3 17:15:32 2015 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 December 2014.