



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 3800 64X 400MHz R12k

SPECfp_rate2000 = 265
SPECfp_rate_base2000 = 248

SPEC license #: 4 Tested by: SGI Test date: Jul-2000 Hardware Avail: Sep-2000 Software Avail: Sep-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	64	540	220	64	447	266
171.swim	64	1001	230	64	1004	229
172.mgrid	64	720	186	64	696	192
173.applu	64	788	198	64	735	212
177.mesa	64	481	216	64	454	229
178.galgel	64	292	738	64	253	849
179.art	64	255	758	64	259	746
183.equake	64	523	185	64	513	188
187.facerec	64	449	314	64	442	319
188.amp	64	563	290	64	565	289
189.lucas	64	722	206	64	722	206
191.fma3d	64	1026	152	64	884	176
200.sixtrack	64	595	137	64	586	139
301.apsi	64	960	201	64	709	272

Hardware

CPU: R12000
CPU MHz: 400
FPU: Integrated
CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
CPU(s) orderable: 16-512
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 64GB
Disk Subsystem: 1 x 18 GB FC, 6 x 18 GB FC (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.9m
Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90
SCSL 1.2 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):
PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2
Portability Flags:
178.galgel: -fixedform
Peak optimization flags:
note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000 -INLINE:aggressive=on
-OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5
171.swim: -Ofast=ip27 -LNO:cs2=8m
172.mgrid: -Ofast=ip27 -LNO:cs2=8m:blocking=off
173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2
177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0 (FEEDBACK)
178.galgel: -Ofast=ip27 -LNO:ou_max=7 -lscs (FEEDBACK)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 3800 64X 400MHz R12k

SPECfp_rate2000 = 265
SPECfp_rate_base2000 = 248

SPEC license #: 4 | Tested by: SGI | Test date: Jul-2000 | Hardware Avail: Sep-2000 | Software Avail: Sep-2000

Notes/Tuning Information (Continued)

```

.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -IPA:min_hot=15 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -fb_opt /tmp/SPEC2000/FBDIR_peak/$(EXEBASE) -LNO:fusion=2 (FEEDBACK)
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -OPT:goto=off:unroll_size=160:unroll_times_max=4
.
  -CG:ld_latency=2 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
  setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
  systune -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
  limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
  rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe

```