



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Model L3000

SPECint_rate2000 = 8.88
SPECint_rate_base2000 = 8.53

SPEC license #: 3 Tested by: HP Richardson, TX Test date: Nov-2000 Hardware Avail: Nov-2000 Software Avail: Nov-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	383	8.49	2	378	8.58
175.vpr	2	387	8.40	2	363	8.95
176.gcc	2	212	12.1	2	212	12.1
181.mcf	2	691	6.05	2	691	6.04
186.crafty	2	215	10.8	2	215	10.8
197.parser	2	583	7.16	2	579	7.21
252.eon	2	347	8.69	2	312	9.68
253.perlbnk	2	473	8.83	2	437	9.55
254.gap	2	569	4.49	2	569	4.49
255.vortex	2	271	16.3	2	260	17.0
256.bzip2	2	504	6.91	2	440	7.91
300.twolf	2	727	9.58	2	699	9.96

Hardware

CPU: 550 MHz PA-8600
CPU MHz: 550
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1-4
Parallel: No
Primary Cache: 512KBI+1MBD (on chip)
Secondary Cache: none
L3 Cache: none
Other Cache: None
Memory: 8GB
Disk Subsystem: 2x36 GB 10000RPM
Other Hardware: --

Software

Operating System: HP-UX B.11.0
Compiler: HP92453-01 A.11.01.20 HP C Compiler
B3913DB C.03.25 HP aC++ Compiler (S800)
File System: HP-UX HFS
System State: Multi-user

Notes/Tuning Information

Portability flags:

175.vpr: -DSPEC_CPU2000 ; 176.gcc: -DHOST_WORDS_BIG_ENDIAN
181.mcf: -DWANT_STDC_PROTO ; 186.crafty: -DHP -DSPEC_CPU2000
197.parser: -DSPEC_CPU2000 ; 252.eon: -DFMAX_IS_DOUBLE -DNDEBUG
253.perlbnk: -DSPEC_CPU2000_HP ; 254.gap: -DSPEC_CPU2000_HP
-DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DSPEC_CPU2000

Compiler invoked in extended ANSI mode: cc -Ae

Base flags:

cc: +Oall +Ostatic_prediction -Wl,-aarchive +I/+P
c++: +O3 +Ostatic_prediction -Wl,-aarchive +I/+P

Peak flags:

Peak flags = base flags for 186.crafty and 254.gap
all: +Ostaticprediction -Wl,-aarchive +I/+P
164.zip: +Oall +Optrs_strongly_typed +Oinline_budget=800
-Wl,/opt/langtools/lib/fastmem.o
175.vpr: +Oall +Optrs_strongly_typed +Owhole_program_mode
176.gcc: +Oall +ESlit +ESfic
181.mcf: +Oall +Opromote_indirect_calls
186.crafty: basepeak



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Model L3000

SPECint_rate2000 = 8.88
SPECint_rate_base2000 = 8.53

SPEC license #: 3 | Tested by: HP Richardson, TX | Test date: Nov-2000 | Hardware Avail: Nov-2000 | Software Avail: Nov-2000

Notes/Tuning Information (Continued)

```
197.parser: +Oall +Odataprefetch +ESfic +Oinline_budget=400
    252.eon: +noeh +O4 +Optrs_strongly_typed +Olibcalls
253.perlbnk: +Oall +ESlit +ESfic -Wl,/opt/langtools/lib/fastmem.o
    254.gap: basepeak
255.vortex: +Oall +Oinline_budget=800 +Optrs_strongly_typed
    -Wl,/opt/langtools/lib/fastmem.o
    256.bzip2: +Oall +Odataprefetch +Optrs_strongly_typed
    300.twolf: +Oall +Optrs_strongly_typed
Kernel tunables:
vps_pagesize=4096, vps_ceiling=16384, maxdsiz=0X04000000, maxssiz=0X10000000, dbc_max_pct=10, dbc_min_pct=10
Unused processors disabled at boot
Event Monitoring System disabled.
```