



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.3 GHz, Pentium 4 processor)

SPECfp2000 = 511

SPECfp_base2000 = 503

SPEC license #: 13 Tested by: Intel Corporation Test date: Dec-2000 Hardware Avail: Jan-2001 Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	235	680	235	680	
171.swim	3100	250	1238	250	1238	
172.mgrid	1800	360	500	328	548	
173.applu	2100	359	585	359	585	
177.mesa	1400	289	484	293	478	
178.galgel	2900	585	496	585	496	
179.art	2600	506	514	493	527	
183.quake	1300	190	685	176	740	
187.facerec	1900	475	400	471	403	
188.amp	2200	642	343	637	345	
189.lucas	2000	286	700	286	700	
191.fma3d	2100	551	381	551	381	
200.sixtrack	1100	493	223	487	226	
301.apsi	2600	661	393	661	393	

Hardware

CPU: Pentium 4 processor (1.3 GHz, 400 MHz bus)
 CPU MHz: 1300
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
 Disk Subsystem: IBM DTLA-307030 ATA-100
 Other Hardware: Creative Labs Annihilator 2

Software

Operating System: Windows 2000 (Build 2195) Service Pack 1
 Compiler: Intel C/C++ and Fortran Compiler 5.0
 Microsoft Visual C++ 6.0(for libraries)
 Other software: Microquill SmartHeap V5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 +FDO
177.mesa: -Qipo -QxW -Oa -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO shlw32M.lib
183.quake: -Qipo -QxW -Qrcd -Oa +FDO shlw32M.lib
187.facerec: -Qipo -QxW -O3 +FDO shlw32M.lib
188.amp: -Qipo -Oa -QxW -O3 +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.3 GHz, Pentium 4 processor)

SPECfp2000 = 511

SPECfp_base2000 = 503

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Dec-2000 | Hardware Avail: Jan-2001 | Software Avail: Oct-2000

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO
 301.apsi: -Qipo -QxW -O3 +FDO
 Library ordering for 187.facerec (include SmartHeap correctly with default libs):
 LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlW32M.lib
 LIBC.lib libirc.lib OLDNAMES.lib
 shlW32M.lib is the SmartHeap library V5.0 from Microquill: <http://www.microquill.com>
 Tested systems can be used with Shin-G ATX case, Delta Inc. power supply
 Product description located as of 11/2000:
http://developer.intel.com/design/motherbd/gb/gb_ds.htm
 Motherboard is available through Intel OEM Distribution Channel. See
<http://channel.intel.com/business/ibp/boards/d850gb.htm> for more information
 The system bus runs at 400 MHz