



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer DS20E Model 68/833

SPECint2000 = 571
SPECint_base2000 = 497

SPEC license #:	2	Tested by:	Compaq NH	Test date:	Jun-2001	Hardware Avail:	Jun-2001	Software Avail:	Aug-2001
Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	200	400	600	800
164.gzip	1400	358	391	351	399	400	400	400	400
175.vpr	1400	313	448	311	451	400	400	400	400
176.gcc	1100	184	597	165	667	400	400	400	400
181.mcf	1800	374	481	290	620	400	400	400	400
186.crafty	1000	145	687	145	687	400	400	400	400
197.parser	1800	497	362	404	445	380	400	400	400
252.eon	1300	194	670	193	674	400	400	400	400
253.perlbench	1800	623	289	322	559	350	350	350	350
254.gap	1100	296	372	251	438	380	400	400	400
255.vortex	1900	278	683	243	783	400	400	400	400
256.bzip2	1500	276	544	255	588	350	350	350	350
300.twolf	3000	442	679	433	693	400	400	400	400

Hardware

CPU: Alpha 21264B
 CPU MHz: 833
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1 to 2
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 8MB off chip per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 4GB
 Disk Subsystem: 1x18GB
 Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1
 +Patch Kit 2
 Compiler: Compaq C V6.4-214-46B59
 Program Analysis Tools V2.0
 Spike V5.2 DTK (1.461 46B5P)
 Compaq C++ V6.3-010-46B2F
 File System: AdvFS
 System State: Multi-user

Notes/Tuning Information

Baseline C : cc -arch ev6 -fast +CFB ONESTEP
 C++: cxx -arch ev6 -O2 ONESTEP

Peak:

```
All but 252.eon: cc -g3 -arch ev6 ONESTEP
164.gzip: -fast -O4 -non_shared +CFB
175.vpr: -fast -O4 -assume restricted_pointers +CFB
176.gcc: -fast -O4 -xtaso_short -all -ldensemalloc -none
+CFB +IFB
181.mcf: -fast -xtaso_short +CFB +IFB +PFB
186.crafty: same as base
197.parser: -fast -O4 -xtaso_short -non_shared +CFB
252.eon: cxx -arch ev6 -O2 -all -ldensemalloc -none
253.perlbench: -fast -non_shared +CFB +IFB
254.gap: -fast -O4 -non_shared +CFB +IFB +PFB
255.vortex: -fast -non_shared +CFB +IFB
256.bzip2: -fast -O4 -non_shared +CFB
300.twolf: -fast -O4 -assume restricted_pointers -all
-ldensemalloc -none +CFB +IFB
```

Most benchmarks are built using one or more types of



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer DS20E Model 68/833

SPECint2000 = 571
SPECint_base2000 = 497

SPEC license #: 2

Tested by:

Compaq NH

Test date:

Jun-2001

Hardware Avail:

Jun-2001

Software Avail:

Aug-2001

Notes/Tuning Information (Continued)

profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```
mkdir /tmp/pp
rm -f /tmp/pp/${baseeexe}*
```

and these flags are added to the first and second compiles:

```
PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp
```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```
mv ${baseeexe} oldexe
spike oldexe -feedback oldexe -o ${baseeexe}
```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```
rm -f *Counts*
mv ${baseeexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseeexe}
```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```
spike oldexe -fb oldexe -stride_prefetch -o ${baseeexe}
```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: gcc: -Dalloca=__builtin_alloca; crafty: -DALPHA
perlchk: -DSPEC_CPU2000_DUNIX; vortex: -DSPEC_CPU2000_LP64
gap: -DSYS_HAS_CALLOC_PROTO -DSYS_IS_BSD -DSYS_HAS_IOCTL_PROTO
-DSPEC_CPU2000_LP64

Information on UNIX V5.1 Patches can be found at
<http://ftp1.service.digital.com/public/unix/v5.1/>

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a beta kit in August, 2001, and as a production release in October, 2001. The C compiler for this SPEC submission has been



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Compaq Computer Corporation
AlphaServer DS20E Model 68/833

SPECint2000 = 571
SPECint_base2000 = 497

SPEC license #: 2

Tested by:

Compaq NH

Test date:

Jun-2001

Hardware Avail:

Jun-2001

Software Avail:

Aug-2001

Notes/Tuning Information (Continued)

available at the same location, as a production release, since May, 2001.

All of the benchmarks were compiled with the "-v" flag. This flag turns on "verbose mode" when compiling, and has no impact on performance.