



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER600 (600MHz)

SPECint_rate2000 = 19.0
SPECint_rate_base2000 = 17.3

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Sep-2001 Hardware Avail: Aug-2001 Software Avail: Dec-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	469	13.9	4	394	16.5
175.vpr	4	398	16.3	4	382	17.0
176.gcc	4	410	12.5	4	287	17.8
181.mcf	4	441	18.9	4	428	19.5
186.crafty	4	252	18.4	4	220	21.1
197.parser	4	456	18.3	4	443	18.9
252.eon	4	333	18.1	4	287	21.0
253.perlbnk	4	417	20.0	4	407	20.5
254.gap	4	501	10.2	4	487	10.5
255.vortex	4	324	27.2	4	316	27.9
256.bzip2	4	373	18.7	4	372	18.7
300.twolf	4	636	21.9	4	592	23.5

Hardware

CPU: SPARC64 GP
 CPU MHz: 600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2 to 8
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 8MB(I+D) off chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 8192MB
 Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
 Other Hardware: None

Software

Operating System: Solaris 8 7/01
 Compiler: Fujitsu Parallelnavi 1.0.2
 with patch 911403-01
 Sun Forte Developer 6 update 2
 File System: ufs
 System State: single user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.2): -Kfast_GP=3,largepage
 fdo_pre0=rm -rf `pwd`/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=\$(EXEBASE).fbk
 (252.eon, for Forte Developer 6 update 2): -fast -xcrossfile -xarch=v8plus
 fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
 PASS1=-xprofile=collect:`pwd`/../feedback
 PASS2=-xprofile=use:`pwd`/../feedback

Peak (for Parallelnavi 1.0.2):
 fdo_pre0=rm -rf `pwd`/*.fbk
 PASS1=-Kpg
 PASS2=-Kpu=\$(EXEBASE).fbk
 164.gzip: -Kfast_GP=4,largepage
 175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLTD=3,xi=30
 181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=2,largepage -x-
 197.parser: -Kfast_GP=4,switchopt,cond,staticclump,use_rodata,largepage
 253.perlbnk: -Kfast_GP=4,memalias,switchopt,largepage,bcopy
 254.gap: -Kfast_GP=3,largepage,memalias,unroll=4
 256.bzip2: -Kfast_GP=3,largepage



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER600 (600MHz)

SPECint_rate2000 = 19.0
SPECint_rate_base2000 = 17.3

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Sep-2001 | Hardware Avail: Aug-2001 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```

300.twolf: -Kfast_GP=5,GREG,memalias,cfunc,staticclump,use_rodata,xi=10,largepage,nounroll,bcopy
(for Forte Developer 6 update 2)
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
-xarch=v8plus -xprefetch -DUSG
186.crafty: -fast -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong
-xregs=syst -xchip=ultra2 -xarch=v8plus -W2,-Amemopt
252.eon: -fast -xcrossfile -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
-Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Msl,-Mt500,-Mr6000,-crit
-Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
-xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus -W2,-Amemopt

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon: -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_CALLOC_PROTO

```

Note:

```

System Tunables: (for /etc/system)
consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
shmsys:shminfo_shmmax=8589934592, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024
(for /etc/opt/FJSPvnm/lpg.conf)
TSS=512M, SHMSEGSIZE=256M
ONESTEP=yes was set for all baseline and peak benchmarks.
Feedback directed optimization was used for all baseline and peak benchmarks.

```