



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp server rp7400

SPECfp_rate2000 = 19.3

SPECfp_rate_base2000 = 17.3

SPEC license #: 3 Tested by: HP Richardson Test date: Oct-2001 Hardware Avail: Sep-2001 Software Avail: Sep-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	570	13.0	4	341	21.8
171.swim	4	682	21.1	4	682	21.1
172.mgrid	4	514	16.2	4	514	16.2
173.applu	4	568	17.2	4	568	17.2
177.mesa	4	281	23.1	4	279	23.3
178.galgel	4	258	52.2	4	258	52.2
179.art	4	649	18.6	4	440	27.4
183.equake	4	649	9.30	4	481	12.5
187.facerec	4	655	13.5	4	635	13.9
188.amp	4	534	19.1	4	467	21.8
189.lucas	4	758	12.2	4	731	12.7
191.fma3d	4	891	10.9	4	881	11.1
200.sixtrack	4	314	16.2	4	280	18.2
301.apsi	4	518	23.3	4	518	23.3

Hardware

CPU: PA-8700
CPU MHz: 650
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 1 to 8
Parallel: No
Primary Cache: 0.75MBI + 1.5MBD on chip
Secondary Cache: None
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 2x9GB SCSI disk
Other Hardware: None

Software

Operating System: B.11.11.0109.6 HP-UX 11i, September 2001 HWE patches
Compiler: HP ANSI C 11.11.03
aC++ C.03.30.02
Fortran90 11.11.40
PHSS_24207 libm patch
File System: HFS
System State: Multi-user

Notes/Tuning Information

Portability Flags:

178.galgel: +source=fixed

Base Flags:

f90: +O3 +Onofltacc -Wl,-a,archive -Wl,+FPD
C: +I/+P +O4 +Odataprefetch -Wl,-a,archive

Peak Flags:

ONESTEP=true for 168.wupwise, 187.facerec, 200.sixtrack

168.wupwise: +cat +O3 +Odataprefetch +Onofltacc
-Wl,+FPD -Wl,-a,archive

171.swim: basepeak=true

172.mgrid: basepeak=true

173.applu: basepeak=true



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp server rp7400

SPECfp_rate2000 = 19.3

SPECfp_rate_base2000 = 17.3

SPEC license #: 3 | Tested by: HP Richardson | Test date: Oct-2001 | Hardware Avail: Sep-2001 | Software Avail: Sep-2001

Notes/Tuning Information (Continued)

```

177.mesa: +I/+P +Oall +Odataprefetch +Opromote_indirect_calls
          -Wl,+FPD -Wl,-a,archive
178.galgel: basepeak=true
179.art: +I/+P +Oall +Onodataprefetch +Onofltacc
          +Optrs_strongly_typed +Opromote_indirect_calls
          -Wl,+FPD -Wl,-a,archive
183.quake: +O4 +Olibcalls +Odataprefetch +Optrs_strongly_typed
            +Opromote_indirect_calls
            -Wl,+FPD -Wl,-a,archive
187.facerec: +cat +O3 +Ofastaccess
             -Wl,+FPD -Wl,-a,archive
188.ammp: +I/+P +Oall +Odataprefetch +Optrs_strongly_typed
           +Opromote_indirect_calls
           -Wl,+FPD -Wl,-a,archive
189.lucas: +O3 +Onoinline
           -Wl,+FPD -Wl,-a,archive
191.fma3d: +O3 +Onolimit
           -Wl,+FPD -Wl,-a,archive
200.sixtrack: +cat +O3 +Onolibcalls +Onolimit +Onoinline
              +Onodataprefetch
              -Wl,+FPD -Wl,-a,archive
301.apsi: basepeak=true

```

System tunables:

```

vps_pagesize 4096, vps_ceiling 16384
dbc_min_pct 20, dbc_max_pct 20
maxdsiz 2063835136, maxssiz 401604608
Unused processors disabled at boot

```