



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 SP-450MHz T/W(1 CPU)

SPECint2000 = 334
SPECint_base2000 = 313

SPEC license #: 11 Tested by: IBM Corp. Test date: Oct-2001 Hardware Avail: Jan-2002 Software Avail: Dec-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	530	264	532	263	
175.vpr	1400	440	318	435	322	
176.gcc	1100	328	336	328	336	
181.mcf	1800	357	504	357	504	
186.crafty	1000	359	278	278	360	
197.parser	1800	897	201	824	219	
252.eon	1300	331	393	331	393	
253.perlbnk	1800	777	232	671	268	
254.gap	1100	403	273	403	273	
255.vortex	1900	640	297	505	376	
256.bzip2	1500	473	317	457	328	
300.twolf	3000	634	473	618	485	

Hardware

CPU: POWER3-II
 CPU MHz: 450
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 32KBI+64KBD (on chip)
 Secondary Cache: 8MB unified (off chip)
 L3 Cache: None
 Other Cache: None
 Memory: 2GB
 Disk Subsystem: 2x18GB 10000RPM
 Other Hardware: None

Software

Operating System: AIX 5L V5.1
 Compiler: C: IBM VAC++ 5.0.2.0 invoked as cc except where noted as xlc
 C++: IBM VAC++ 5.0.2.0 invoked as xlc
 File System: AIX/JFS
 System State: Multi-user

Notes/Tuning Information

Portability Flags:

```
gcc:      -ma -qlanglvl=ansi -DHOST_WORDS_BIG_ENDIAN
crafty:   -DAIX
eon:      -DNEED_EXPLICIT_SPECIALIZATION
perlbnk:  -DSPEC_CPU2000_AIX
gap:      -DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
twolf:    -DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C:        -O4 -lmass
C++:      -O4 -lmass
```

Peak Optimization Flags

```
164.gzip: -O4 -lhmu, fdpr -R3 -p -x -o
175.vpr:  -O5 -qunroll=8
176.gcc:  (basepeak=1)
181.mcf:  (basepeak=1)
186.crafty: -O3 -lhmu -q64
197.parser: -qpdf1/pdf2 -O4 -lpdf
          -bnso -bI:/lib/syscalls.exp, fdpr -R3 -p -x
252.eon:  -O4 -lmass, fdpr -R3 -p -x -o
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 SP-450MHz T/W(1 CPU)

SPECint2000 = 334
SPECint_base2000 = 313

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Oct-2001 | Hardware Avail: Jan-2002 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```
253.perlbnk: -qpdf1/pdf2 -O3 -lhmu -lpdf -qarch=pwr3
              -qdatalocal -qunroll=8, fdpr -R3 -p -x
254.gap:      -O4 -qarch=pwr3, fdpr -R3 -p -x -o
255.vortex:   -O3 -lhmu -lmass -qipa=partition=large,
              fdpr -v -R3 -p -x
256.bzip2:    -O5 -qunroll=8, fdpr -R3 -p -x -o
300.twolf:    -qpdf1/pdf2 -O5 -lpdf, fdpr -R3 -p -x
              CC=/usr/vac/bin/xlc
fpdr: Feedback directed program restructuring tool
APAR IY 21957 was applied to AIX 5L V5.1 to enable new hardware support
```