



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 610 Mod 6C1 333MHz

SPECfp_rate2000 = 7.10

SPECfp_rate_base2000 = 7.04

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jan-2002 | Hardware Avail: Feb-2002 | Software Avail: Feb-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	331	11.2	2	331	11.2
171.swim	2	1147	6.27	2	1147	6.27
172.mgrid	2	718	5.81	2	718	5.81
173.applu	2	829	5.88	2	832	5.86
177.mesa	2	593	5.48	2	587	5.53
178.galgel	2	435	15.5	2	435	15.5
179.art	2	444	13.6	2	444	13.6
183.quake	2	352	8.57	2	338	8.92
187.facerec	2	573	7.69	2	573	7.69
188.amp	2	892	5.72	2	871	5.86
189.lucas	2	909	5.10	2	895	5.18
191.fma3d	2	799	6.09	2	774	6.30
200.sixtrack	2	675	3.78	2	675	3.78
301.apsi	2	1012	5.96	2	1012	5.96

Hardware

CPU: POWER3-II
CPU MHz: 333
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KBI+64KBD (on chip)
Secondary Cache: 4MB unified (off chip)
L3 Cache: None
Other Cache: None
Memory: 2GB
Disk Subsystem: 2x18GB 10000RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.1
Compiler: IBM XL FORTRAN for AIX, Version 7.1.1.0
IBM VisualAge C++ for AIX, Version 5.0.2.1
File System: AIX/JFS
System State: Multi-user

Notes/Tuning Information

Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:

Fortran: -O5 -lmass
C: -O5 -lmass

Peak Optimization Flags

168.wupwise: (basepeak=1)
171.swim: (basepeak=1)
172.mgrid: (basepeak=1)
173.applu: -O5 -lmass -qipa=partition=large
177.mesa: -O5 -lmass -qipa=partition=large, fdpr -v -R3
178.galgel: (basepeak=1)
179.art: (basepeak=1)
183.quake: -O5 -lmass -lhmu -qinline
187.facerec: (basepeak=1)
188.amp: -O3 -qarch=pwr3



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 610 Mod 6C1 333MHz

SPECfp_rate2000 = 7.10

SPECfp_rate_base2000 = 7.04

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Jan-2002 | Hardware Avail: Feb-2002 | Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```
189.lucas:      -qpdf1/pdf2 -O3 -lhm -lmas
                -qipa=partition=large, fdpr -v -R3
191.fma3d:      -O4 -lmas -qipa=partition=large
200.sixtrack:   (basepeak=1)
301.apsi:       (basepeak=1)
fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O
APAR IY22854 was applied to AIX 5L V5.1 to enable new hardware support
ulimits set to unlimited
Fortran 77 and 90: IBM xl Fortran 7.1.1.0 invoked
as xlf90 for Fortran 90 and as xlf for Fortran 77
C: IBM VAC++ 5.0.2.1 invoked as xlc
```