



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 600MHz R14000A

SPECfp_rate2000 = 38.7
SPECfp_rate_base2000 = 36.4

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	405	36.7	8	364	40.8
171.swim	8	994	28.9	8	979	29.4
172.mgrid	8	726	23.0	8	712	23.5
173.applu	8	685	28.5	8	622	31.3
177.mesa	8	339	38.3	8	308	42.2
178.galgel	8	230	117	8	201	134
179.art	8	217	111	8	216	112
183.equake	8	518	23.3	8	511	23.6
187.facerec	8	462	38.2	8	461	38.2
188.amp	8	401	50.9	8	399	51.2
189.lucas	8	723	25.7	8	712	26.1
191.fma3d	8	875	22.3	8	803	24.3
200.sixtrack	8	377	27.1	8	374	27.3
301.apsi	8	807	29.9	8	625	38.6

Hardware

CPU: R14000A
CPU MHz: 600
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2-32
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 4MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB
Disk Subsystem: 1 x 18 GB FC, 2 x 18 GB FC (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.16m
Compiler: MIPSpro 7.3.1.3m C, Fortran90
SCSL 1.4 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):
PASS1 : -Ofast=ip35 -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
PASS2 : -Ofast=ip35 -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)
Baseline optimization flags (for Fortran benchmarks): -Ofast=ip35 -LNO:fusion=2
Portability Flags:
178.galgel: -fixedform
Peak optimization flags:
note: all occurrences of (FEEDBACK) below means compiled with a two-step process:
PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
168.wupwise: -Ofast=ip35 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000
-INLINE:aggressive=on -OPT:Olimit=0 -LNO:fusion=2:prefetch_ahead=5
171.swim: -Ofast=ip35 -CG:ld_latency=10
172.mgrid: -Ofast=ip35 -LNO:fusion=2
173.applu: -Ofast=ip35 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2 -CG:ld_latency=3
177.mesa: -Ofast=ip35 -OPT:goto=off -LNO:opt=0 -CG:ld_latency=6 (FEEDBACK)
178.galgel: -Ofast=ip35 -LNO:ou_max=7 -CG:ld_latency=3 -lscs (FEEDBACK)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 600MHz R14000A

SPECfp_rate2000 = 38.7
SPECfp_rate_base2000 = 36.4

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

```

RM_SOURCES = lapak.f90
179.art: -Ofast=ip35 -LNO:prefetch=0 -IPA:min_hot=15 -CG:ld_latency=3 (FEEDBACK)
183.equake: -Ofast=ip35 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip35 -LNO:fusion=2
188.ammp: -Ofast=ip35 -OPT:goto=off -IPA:space=500:plimit=900 -CG:ld_latency=7 (FEEDBACK)
189.lucas: -Ofast=ip35 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip35 -bigp_off -LNO:prefetch=0 -CG:ld_latency=2
-OPT:goto=off:unroll_size=160:unroll_times_max=4 (FEEDBACK)
200.sixtrack:= -Ofast=ip35 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip35 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
The following O/S parameters were set:
setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
systune -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
systune -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
systune -i ; r12k_bdiag = 0x4000000
limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
Jobs are submitted using dplace. Contents of the placement file submit.pf:
memories 1 in topology physical near $NODE
threads 1
run thread 0 on memory 0 using cpu $CPU
The first disk mentioned in the Disk Subsystem is the system disk. A striped
XFS filesystem was created using the rest of the disks and the benchmark was
run on this.

```