



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp_rate2000 = 49.2

SPECfp_rate_base2000 = 44.2

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	155	47.8	4	142	52.1
171.swim	4	206	69.8	4	179	80.5
172.mgrid	4	205	40.8	4	194	43.1
173.applu	4	260	37.5	4	228	42.7
177.mesa	4	117	55.7	4	114	57.1
178.galgel	4	221	60.9	4	162	83.0
179.art	4	296	40.8	4	231	52.2
183.quake	4	179	33.8	4	129	46.8
187.facerec	4	184	47.9	4	179	49.3
188.amp	4	214	47.6	4	219	46.5
189.lucas	4	185	50.2	4	179	52.0
191.fma3d	4	213	45.6	4	213	45.6
200.sixtrack	4	247	20.7	4	226	22.6
301.apsi	4	286	42.2	4	269	44.9

Hardware

CPU: AMD Opteron 844, 1.8 GHz
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16x512MB PC2700 DDR ECC Registered SDRAM CL2.5
Disk Subsystem: IDE 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition
Compiler: Intel C/C++ 7.0 build 20021212Z and Intel Fortran 7.0 build 20021212Z
Compaq Visual Fortran Compiler Version 6.6 (Update B)
Microsoft Visual Studio .NET (libraries)7.0.9466
MicroQuill Smartheap Library 6.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
Portability:
  178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C      icl +FDO -O3 -QxW -Qipo
Baseline: Fortran ifl +FDO -O3 -QxW -Qipo
Peak tuning:
  168.wupwise:   ifl +FDO      -QxK  -Qipo -Ow
  171.swim:      f90 -Optimize:5 -alignment:dcommons -alignment:records
                  -alignment:sequence -architecture:k7
                  -assume:noaccuracy_sensitive -math_library:fast -tune:k7
  172.mgrid:     ifl +FDO -O3 -QaxW -Qipo -Oa -Qprefetch-
  173.applu:     ifl +FDO -O3 -QxK  -Qipo      -Qscalar_rep-      -Zp8
  177.mesa:      icl +FDO -O3 -QxW  -Qipo -Oa -Qscalar_rep-
  178.galgel:    f90 -Optimize:5 -fast
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp_rate2000 = 49.2

SPECfp_rate_base2000 = 44.2

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```
179.art:      icl      -Qipo -Oa      -Qunroll14 -Zp4
183.quake:   icl      -O3 -QxK -Qipo -Oa shlw32M6.lib -Zp4
187.facerec: ifl +FD0 -O3 -QaxW -Qipo -Qscalar_rep- -Qunroll11
188.ampp:    icl      -QxW -Oa
189.lucas:   ifl +FD0 -O3 -QxW -Qipo -Qprefetch-
191.fma3d:   ifl basepeak=1
200.sixtrack: ifl      -Qipo -Oa      -Zp4
301.apsi:    f90 -Optimize:5 -fast
ONESTEP is used for all base and peak runs
```