



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity Server rx5670 (1500 MHz, Itanium 2)

SPECfp_rate2000 = 24.5
SPECfp_rate_base2000 = 24.5

SPEC license #: 3 Tested by: HP Richardson Test date: Jun-2003 Hardware Avail: Sep-2003 Software Avail: Sep-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	112	16.5	1	112	16.5
171.swim	1	73.8	48.7	1	73.8	48.7
172.mgrid	1	71.8	29.1	1	71.8	29.1
173.applu	1	61.7	39.5	1	61.7	39.5
177.mesa	1	122	13.3	1	122	13.3
178.galgel	1	68.3	49.3	1	68.3	49.3
179.art	1	39.0	77.4	1	39.0	77.4
183.quake	1	44.6	33.8	1	44.6	33.8
187.facerec	1	97.0	22.7	1	97.0	22.7
188.amp	1	155	16.4	1	155	16.4
189.lucas	1	114	20.3	1	114	20.3
191.fma3d	1	199	12.3	1	199	12.3
200.sixtrack	1	80.0	15.9	1	80.0	15.9
301.apsi	1	260	11.6	1	260	11.6

Hardware

CPU: Intel Itanium 2
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-4
Parallel: no
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 6.0MB (on chip) per CPU
Other Cache: N/A
Memory: 24GB (48 x 512MB DIMMs on 2 memory carriers)
Disk Subsystem: 1x36GB 15k RPM SCSI disk
Other Hardware: N/A

Software

Operating System: Red Hat Linux Advanced Server 2.1 (Update 2)
Compiler: Intel C++ Compiler 7.1 for Linux64, Build 20030519
Intel Fortran Compiler 7.1 for Linux64, Build 20030519
File System: ext3
System State: Multi-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen PASS2=-prof_use
Base tuning flags:
    C programs: -ipo -O3 +FDO -ansi_alias
    Fortran programs: -ipo -O3 +FDO
Portability:
    178.galgel: -FI

Peak flags same as baseline (basepeak=true set globally)
```

Note:
'ELILO boot: linux maxcpus=0' used to
deconfigure other processors if necessary
Kernel was built with the configuration of 64K page size.