



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.06 GHz Xeon)

SPECint_rate2000 = 27.0

SPECint_rate_base2000 = 25.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	118	27.6	2	117	27.7
175.vpr	2	181	17.9	2	181	17.9
176.gcc	2	80.0	31.9	2	79.3	32.2
181.mcf	2	350	11.9	2	352	11.9
186.crafy	2	85.1	27.3	2	85.1	27.3
197.parser	2	162	25.8	2	162	25.8
252.eon	2	95.9	31.4	2	82.7	36.5
253.perlbnk	2	135	30.9	2	131	31.9
254.gap	2	79.2	32.2	2	79.2	32.2
255.vortex	2	108	40.8	2	108	40.8
256.bzip2	2	175	19.9	2	172	20.3
300.twolf	2	275	25.3	2	195	35.7

Hardware

CPU: Intel Pentium Xeon (533 MHz system bus)
 CPU MHz: 3066
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4 X 512MB DDR266
 Disk Subsystem: 1 x 17GB Ultra3 Seagate SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Server (SP2)
 Compiler: Intel C++ Compiler 7.1 (20030402Z)
 Microsoft Visual Studio .NET (7.0.9466)
 MicroQuill SmartHeap Library 6.01
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

BASE TUNING

C: -QxW -Qipo -O3 +FDO
 C++: -QxW -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxW -Qipo -Oa -O3 +FDO
 175.vpr: -QxW -Qipo -O3 +FDO
 176.gcc: -QxW -Qipo -O3 +FDO
 181.mcf: -QxW -Qipo -O3 +FDO shlw32M.lib
 186.crafy: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 197.parser: -QxW -Qipo -O3 +FDO
 252.eon: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 253.perlbnk: -QxW -Qipo -O3 +FDO shlw32M.lib
 254.gap: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.06 GHz Xeon)

SPECint_rate2000 = 27.0

SPECint_rate_base2000 = 25.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Apr-2003

Notes/Tuning Information (Continued)

```
255.vortex    basepeak=yes
256.bzip2:    -Qipo -Oa -Qunroll1 +FDO
300.twolf:    -Qipo -QxW -O3 -Oa      shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 6.01
              www.microquill.com
ONESTEP=YES is set for all benchmarks
```