



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880 (1200MHz)

SPECint_rate2000 = 62.8
SPECint_rate_base2000 = 55.1

SPEC license #: 6 Tested by: Sun Microsystems Test date: Sep-2003 Hardware Avail: Sep-2003 Software Avail: Aug-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	298	43.6	8	246	52.9
175.vpr	8	276	47.2	8	257	50.6
176.gcc	8	194	52.6	8	157	65.0
181.mcf	8	368	45.4	8	303	55.2
186.crafty	8	152	61.2	8	130	71.5
197.parser	8	323	51.7	8	280	59.7
252.eon	8	170	70.8	8	162	74.5
253.perlbnk	8	287	58.2	8	262	63.8
254.gap	8	278	36.7	8	226	45.1
255.vortex	8	203	87.0	8	181	97.7
256.bzip2	8	221	63.1	8	205	67.8
300.twolf	8	463	60.2	8	427	65.1

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2,4,8
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 16GB 8-way interleaved
Disk Subsystem: 1 x 36GB SEAGATE ST336605FSUN36G
Other Hardware: None

Software

Operating System: Solaris 9 8/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:
C: cc
CXX: CC

Integer base flags:
-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
175.vpr: -fast -xalias_level=std -xipo=2
-Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
Feedback adds -xlinkopt in PASS2



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880 (1200MHz)

SPECint_rate2000 = 62.8
SPECint_rate_base2000 = 55.1

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Sep-2003 | Hardware Avail: Sep-2003 | Software Avail: Aug-2003

Notes/Tuning Information (Continued)

```

197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -l12amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

set autoup=900
set tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind