



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECfp_rate2000 = 19.6
SPECfp_rate_base2000 = 19.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2003 | Hardware Avail: Oct-2003 | Software Avail: Sep-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	119	31.1	2	120	30.8
171.swim	2	401	17.9	2	401	18.0
172.mgrid	2	233	17.9	2	232	18.0
173.applu	2	315	15.5	2	313	15.6
177.mesa	2	109	29.8	2	110	29.5
178.galgel	2	220	30.6	2	220	30.6
179.art	2	680	8.88	2	651	9.26
183.quake	2	167	18.1	2	132	22.8
187.facerec	2	160	27.6	2	158	27.9
188.amp	2	324	15.8	2	324	15.8
189.lucas	2	254	18.2	2	254	18.3
191.fma3d	2	248	19.6	2	248	19.6
200.sixtrack	2	188	13.5	2	185	13.8
301.apsi	2	321	18.8	2	315	19.2

Hardware

CPU: Intel Xeon (3.2GHz, 533MHz bus)
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4x512MB PC2100
 Disk Subsystem: 2x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Server(Build 2195 SP3)
 Compiler: Intel C++ Compiler 7.1 Build 20030813Z
 Intel Fortran Compiler 7.1 build 20030813Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Hyper Threading disabled in BIOS

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxW -Qipo -O3 +FDO ONESTEP=yes
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW +FDO ONESTEP=yes
171.swim: -Qipo -QxW -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxW -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxW -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxW -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxW -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxW -O3 -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxW -Oa ONESTEP=yes
189.lucas: -Qipo -QaxW
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECfp_rate2000 = 19.6

SPECfp_rate_base2000 = 19.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2003 | Hardware Avail: Oct-2003 | Software Avail: Sep-2003

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO ONESTEP=yes
301.apsi: -Qipo -QxW -O3 +FDO ONESTEP=yes