



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices  
ASUS SK8N Motherboard, AMD Opteron (TM) 148

SPECfp2000 = 1490  
SPECfp\_base2000 = 1393

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Nov-2003 Hardware Avail: Dec-2003 Software Avail: Dec-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	109	1464	99.9	1601	
171.swim	3100	153	2027	132	2343	
172.mgrid	1800	144	1248	142	1266	
173.applu	2100	178	1182	165	1270	
177.mesa	1400	90.1	1554	88.3	1586	
178.galgel	2900	141	2051	121	2400	
179.art	2600	154	1692	143	1824	
183.quake	1300	109	1191	93.4	1391	
187.facerec	1900	118	1606	115	1646	
188.amp	2200	160	1371	157	1400	
189.lucas	2000	115	1739	115	1740	
191.fma3d	2100	156	1350	156	1350	
200.sixtrack	1100	205	538	183	602	
301.apsi	2600	196	1328	186	1396	

### Hardware

CPU: AMD Opteron (TM) 148  
CPU MHz: 2200  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip  
Secondary Cache: 1024KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 2x512MB PC3200 DDR SDRAM, ECC Registered  
Disk Subsystem: Western Digital WD2000, IDE  
Other Hardware: None

### Software

Operating System: Microsoft Windows XP Professional SP1a  
Compiler: Intel C/C++ 7.0 build 20021212Z and Intel Fortran 7.0 build 20021212Z  
Compaq Visual Fortran Compiler Version 6.6 (Update B)  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill SmartHeap Library 6.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
Portability:
178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C icl +FDO -O3 -QxW -Qipo
Baseline: Fortran ifl +FDO -O3 -QxW -Qipo
Peak tuning:
168.wupwise: ifl +FDO -QxK -Qipo -Ow
171.swim: f90 -Optimize:5 -alignment:dcommons -alignment:records
          -alignment:sequence -architecture:k7
          -assume:noaccuracy_sensitive -math_library:fast -tune:k7
172.mgrid: ifl +FDO -O3 -QaxW -Qipo -Oa -Qprefetch-
173.applu: ifl +FDO -O3 -QxK -Qipo -Qscalar_rep- -Zp8
177.mesa: icl +FDO -O3 -QxW -Qipo -Oa -Qscalar_rep-
178.galgel: f90 -Optimize:5 -fast
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices  
ASUS SK8N Motherboard, AMD Opteron (TM) 148

SPECfp2000 = 1490  
SPECfp\_base2000 = 1393

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Nov-2003 | Hardware Avail: Dec-2003 | Software Avail: Dec-2002

## Notes/Tuning Information (Continued)

```

179.art:          icl          -Qipo -Oa          -Qunroll14 -Zp4
183.equake:      icl          -O3 -QxK  -Qipo -Oa  shlw32M6.lib -Zp4
187.facerec:     ifl +FDO -O3 -QaxW -Qipo          -Qscalar_rep- -Qunroll11
188.ampp:        icl          -QxW          -Oa
189.lucas:       ifl +FDO -O3 -QxW  -Qipo          -Qprefetch-
191.fma3d:       ifl basepeak=1
200.sixtrack:    ifl          -Qipo -Oa          -Zp4
301.apsi:        f90 -Optimize:5 -fast

```

ONESTEP is used for all base and peak runs

The tested system can be assembled using an ATX case such as the Antec KS-282, a 480W power supply, and a PCI or AGP video card.