



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
Precision Workstation 650 (2.40 GHz Xeon, 1MB L3 Cache)

SPECint2000 = **1123**
SPECint_base2000 = **1089**

SPEC license #: 55 Tested by: Dell Inc., Round Rock, TX Test date: Jan-2004 Hardware Avail: Feb-2004 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	140	999	140	997	
175.vpr	1400	182	767	182	767	
176.gcc	1100	82.0	1341	82.0	1341	
181.mcf	1800	193	931	193	934	
186.crafty	1000	106	943	105	952	
197.parser	1800	181	994	181	994	
252.eon	1300	104	1255	91.2	1426	
253.perlbmk	1800	163	1101	155	1160	
254.gap	1100	84.9	1296	84.9	1296	
255.vortex	1900	98.5	1929	98.5	1929	
256.bzip2	1500	173	865	171	878	
300.twolf	3000	290	1035	247	1216	

Hardware

CPU: Intel Xeon (533 MHz system bus)
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4 x 512MB ECC CL2-2-2 PC2100 DDR SDRAM
 Disk Subsystem: 1 x 18GB U320 SCSI, 10K RPM
 Other Hardware:

Software

Operating System: Windows XP Professional SP1
 Compiler: Intel C/C++ Compiler 8.0 (20031229Z)
 Microsoft Visual Studio .NET (7.0.9466)
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

ONESTEP=yes
 FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

BASE TUNING

C: -QxN -Qipo -O3 +FDO
 C++: -QxN -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxN -Qipo -O3 -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: -QxN -Qipo -O3 +FDO shlw32M.lib
 186.crafty: -QxN -Qipo -O3 -Oa +FDO shlw32M.lib
 197.parser: basepeak=yes
 252.eon: -QxN -Qipo -O3 +FDO
 253.perlbmk: -QxN -Qipo -O3 +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell

Precision Workstation 650 (2.40 GHz Xeon, 1MB L3 Cache)

SPECint2000 = 1123

SPECint_base2000 = 1089

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    basepeak=yes
256.bzip2:    -Qipo      -Oa -Qunroll1 +FDO shlw32M.lib
300.twolf:    -QxN -Qipo -O3      +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.1
              www.microquill.com
```

NOTES

1 CPU Disabled in the BIOS.
Hyper-Threading Technology not enabled.