



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1850 (3.6GHz, Intel Xeon)

SPECint2000 = **1538**
SPECint_base2000 = **1462**

SPEC license #: 55 Tested by: Dell Inc., Round Rock, TX Test date: Aug-2004 Hardware Avail: Aug-2004 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	118	1182	119	1179	
175.vpr	1400	139	1010	139	1010	
176.gcc	1100	59.6	1846	59.6	1846	
181.mcf	1800	152	1186	150	1199	
186.crafty	1000	76.3	1310	75.1	1332	
197.parser	1800	133	1352	133	1352	
252.eon	1300	75.8	1714	63.0	2063	
253.perlbmk	1800	108	1669	96.4	1868	
254.gap	1100	59.1	1862	59.1	1862	
255.vortex	1900	75.0	2532	75.0	2532	
256.bzip2	1500	136	1107	132	1137	
300.twolf	3000	218	1379	168	1790	

Hardware

CPU: Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
 CPU MHz: 3600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (HT Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 16K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 2GB ECC DDR2-400 SDRAM
 Disk Subsystem: 1x18.2GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows Enterprise Server 2003
 Compiler: Intel C/C++ Compiler 8.0 (20040318Z)
 Microsoft Visual Studio .NET (7.0.9466)
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -QxP -Qipo -O3 +FDO
 C++: -QxP -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxP -Qipo -O3 -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: -QxP -Qipo -O3 +FDO shlw32M.lib
 186.crafty: -QxP -Qipo -O3 -Oa +FDO shlw32M.lib
 197.parser: basepeak=yes
 252.eon: -QxP -Qipo -O3 +FDO
 253.perlbmk: -QxP -Qipo -O3 +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1850 (3.6GHz, Intel Xeon)

SPECint2000 =	1538
SPECint_base2000 =	1462

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Aug-2004 | Hardware Avail: Aug-2004 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    basepeak=yes
256.bzip2:    -Qipo      -Oa -Qunroll1 +FDO shlW32M.lib
300.twolf:    -QxP -Qipo -O3      +FDO shlW32M.lib
EXTRA LIBRARIES
shlW32M.lib:  MicroQuill SmartHeap Library 7.1
              www.microquill.com
```