



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V440 (1600MHz)

SPECfp2000 = 1349  
SPECfp\_base2000 = 1209

SPEC license #: 6 Tested by: Sun Microsystems Test date: Nov-2004 Hardware Avail: Nov-2004 Software Avail: Jan-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	114	1410	109	1472
171.swim	3100	314	987	162	1917
172.mgrid	1800	229	786	229	785
173.applu	2100	211	994	175	1200
177.mesa	1400	156	897	136	1027
178.galgel	2900	139	2083	117	2473
179.art	2600	22.9	11377	20.9	12438
183.earth	1300	74.6	1742	69.1	1882
187.facerec	1900	99.6	1908	99.0	1919
188.amp	2200	372	592	372	591
189.lucas	2000	216	927	216	927
191.fma3d	2100	308	681	276	761
200.sixtrack	1100	204	539	195	565
301.apsi	2600	282	923	282	921

### Hardware

CPU: UltraSPARC IIIi  
CPU MHz: 1600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 2,4  
Parallel: No  
Primary Cache: 32KBI+64KBD on chip  
Secondary Cache: 1MB(I+D) on chip  
L3 Cache: None  
Other Cache: None  
Memory: 4GB 16-way interleaved  
Disk Subsystem: 1 x 73GB  
Other Hardware: None

### Software

Operating System: Solaris 10  
Compiler: Sun Studio 9  
File System: ufs  
System State: Multi-User

## Notes/Tuning Information

### Compiler invocation:

C: cc  
CXX: CC  
F90: f90  
F77: f90

### Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
F90: -fast -xipo=2 with ONESTEP=yes and feedback

### Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
171.swim: -fast -xpad=common:384 -xprefetch=latx:1.6  
-Qoption iropt -Atile:skewp:b6,-Ainline:cs=700  
(no feedback)



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V440 (1600MHz)

SPECfp2000 = 1349  
SPECfp\_base2000 = 1209

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Nov-2004 | Hardware Avail: Nov-2004 | Software Avail: Jan-2005

## Notes/Tuning Information (Continued)

```
172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
          -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.equake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ammp: -fast -xipo=2 -xalias_level=std -lmopt -lm
189.lucas: basepeak=yes
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
              -xprefetch=no
301.apsi: -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```

System Settings:

```
Other CPUs disabled at boot time by using /etc/system
parameter "cpu_bringup_set"
Used asr to disable the memories on unused CPUs.
```