



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E2900 (12 processor)

SPECfp_rate2000 = 194
SPECfp_rate_base2000 = 162

SPEC license #: 6 Tested by: Sun Microsystems Test date: Feb-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

2000 1500 1000 500				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				168.wupwise	24	324	137	24	305	146
				171.swim	24	1354	63.7	24	231	374
				172.mgrid	24	811	61.8	24	811	61.8
				173.applu	24	370	158	24	329	178
				177.mesa	24	178	219	24	159	244
				178.galgel	24	209	386	24	157	514
				179.art	24	40.1	1804	24	38.5	1882
				183.quake	24	241	150	24	241	150
				187.facerec	24	166	318	24	166	318
				188.amp	24	385	159	24	385	159
				189.lucas	24	828	67.2	24	828	67.2
				191.fma3d	24	777	75.3	24	757	77.2
				200.sixtrack	24	261	117	24	237	129
				301.apsi	24	503	144	24	502	144

Hardware

CPU: UltraSPARC IV
CPU MHz: 1350
FPU: Integrated
CPU(s) enabled: 24 cores, 12 chips, 2 cores/chip
CPU(s) orderable: 4,8,12 (order by # of chips)
Parallel: No
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
L3 Cache: None
Other Cache: None
Memory: 96GB
Disk Subsystem: 1 x 73GB
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 9
File System:
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E2900 (12 processor)

SPECfp_rate2000 = 194
SPECfp_rate_base2000 = 162

SPEC license #: 6 Tested by: Sun Microsystems Test date: Feb-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```
172.mgrid: basepeak = yes
173.applu:  -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa:  -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art:   -fast -xipo=2 -xalias_level=std
           -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: basepeak= yes
187.facerec: basepeak= yes
188.ammmp:  basepeak = yes
189.lucas:  basepeak=yes
191.fma3d:  -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -x04 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
           -xprefetch=no
301.apsi:   -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```