



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon processor 3.60 GHz

SPECint_rate2000 = 38.4
SPECint_rate_base2000 = 38.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	119	27.3	2	119	27.3
175.vpr	2	123	26.4	2	123	26.4
176.gcc	2	55.7	45.9	2	55.7	45.9
181.mcf	2	110	37.9	2	110	37.9
186.crafy	2	74.5	31.1	2	74.5	31.1
197.parser	2	124	33.7	2	124	33.7
252.eon	2	57.6	52.4	2	57.6	52.4
253.perlbnk	2	87.3	47.8	2	87.3	47.8
254.gap	2	64.1	39.8	2	64.1	39.8
255.vortex	2	68.8	64.1	2	68.8	64.1
256.bzip2	2	120	29.0	2	120	29.0
300.twolf	2	166	41.9	2	166	41.9

Hardware

CPU: 64-bit Intel Xeon processor (3.60 GHz, 800 MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512 MB DDRII-RAM PC2-3200R
Disk Subsystem: Fujitsu MAS3367NC (SCSI U320 15 krpm)
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ Compiler 8.1 Build 20050405Z
Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries)
SmartHeap Library Version 6.03a from http://www.microquill.com
File System: NTFS
System State: default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved srcalt stdcpp is used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast +FDO shlW32M.lib
for C++ programs: -fast -Qcxx_features +FDO

Peak tuning flags

same as baseline (basepeak=yes set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon processor 3.60 GHz

SPECint_rate2000 = 38.4
SPECint_rate_base2000 = 38.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>