



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 336 (3.4 GHz Intel Xeon)

SPECint_rate2000 = 20.8
SPECint_rate_base2000 = 20.3

SPEC license #: 11 | Tested by: IBM, Research Trinagle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	181	17.9	2	182	17.8
175.vpr	2	230	14.1	2	230	14.1
176.gcc	2	97.7	26.1	2	97.7	26.1
181.mcf	2	213	19.6	2	213	19.6
186.crafty	2	154	15.1	2	153	15.2
197.parser	2	214	19.6	2	214	19.6
252.eon	2	125	24.1	2	124	24.3
253.perlbnk	2	210	19.8	2	195	21.4
254.gap	2	106	24.1	2	106	24.1
255.vortex	2	139	31.8	2	139	31.6
256.bzip2	2	195	17.8	2	198	17.6
300.twolf	2	346	20.1	2	290	24.0

Hardware

CPU: Intel Xeon (3.4 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 512 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 8.1 (20050409)
Intel Fortran Compiler 8.1 (20050405Z)
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -QxP -Qansi_alias +FDO
C++: -QxP -Qipo -Qcxx_features +FDO

PEAK TUNING

164.zip: -fast -QxP -Qansi_alias -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -QxP -Oa +FDO shlW32M.lib
197.parser: basepeak=yes
252.eon: -fast -QxP +FDO
253.perlbnk: -fast -QxP -Qansi_alias +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 336 (3.4 GHz Intel Xeon)

SPECint_rate2000 = 20.8
SPECint_rate_base2000 = 20.3

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: May-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    -fast -QxP +FDO
256.bzip2:    -fast -QxP -Qunroll1 -Oa +FDO
300.twolf:    -fast -QxP +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.3
              www.microquill.com
```