



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G3 (3.333GHz, Intel Xeon)

SPECfp_rate2000 = 14.6
SPECfp_rate_base2000 = 14.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2005 Hardware Avail: Jun-2005 Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	90.1	20.6	1	90.1	20.6
171.swim	1	267	13.5	1	266	13.5
172.mgrid	1	177	11.8	1	177	11.8
173.applu	1	200	12.2	1	199	12.2
177.mesa	1	100	16.2	1	100	16.2
178.galgel	1	113	29.7	1	113	29.8
179.art	1	92.6	32.6	1	92.6	32.6
183.quake	1	123	12.3	1	90.7	16.6
187.facerec	1	152	14.5	1	152	14.5
188.amp	1	199	12.8	1	199	12.8
189.lucas	1	219	10.6	1	219	10.6
191.fma3d	1	215	11.3	1	215	11.3
200.sixtrack	1	182	7.00	1	182	7.00
301.apsi	1	259	11.6	1	259	11.6

Hardware

CPU: Intel Xeon MP (3.333GHz, 1MB L2, 8MB L3, 667MHz bus)
CPU MHz: 3333
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: 8192KB
Other Cache: N/A
Memory: 16x2048MB DDR2-400
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise (Build 3790)
Compiler: Intel C++ Compiler for 32-bit applications, Version 8.1 Build 20050524Z
Intel Fortran Compiler for 32-bit applications, Version 8.1 build 20050517Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning: -fast -Qansi_alias +FDO

Portability flags:
178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -f77rtl +FDO ONESTEP=yes
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes
177.mesa: -fast +FDO ONESTEP=yes
178.galgel: -fast +FDO ONESTEP=yes
179.art: basepeak=1
183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- -fpp +FDO ONESTEP=yes
188.amp: basepeak=1



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G3 (3.333GHz, Intel Xeon)

SPECfp_rate2000 = 14.6

SPECfp_rate_base2000 = 14.2

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2005 | Hardware Avail: Jun-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled