



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Advanced Micro Devices

Pogo Linux, PerformanceWare 3566, AMD Opteron (TM) 852

SPECfp\_rate2000 = 28.7

SPECfp\_rate\_base2000 = 27.3

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: May-2005 | Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	77.4	48.0	2	77.4	48.0
171.swim	2	285	25.2	2	244	29.5
172.mgrid	2	205	20.4	2	205	20.4
173.applu	2	221	22.0	2	194	25.1
177.mesa	2	76.7	42.3	2	71.8	45.2
178.galgel	2	138	48.7	2	130	51.8
179.art	2	330	18.3	2	282	21.4
183.quake	2	125	24.2	2	125	24.2
187.facerec	2	135	32.6	2	138	32.0
188.amp	2	245	20.8	2	232	22.0
189.lucas	2	176	26.4	2	167	27.8
191.fma3d	2	186	26.1	2	175	27.8
200.sixtrack	2	140	18.2	2	140	18.2
301.apsi	2	204	29.6	2	204	29.6

### Hardware

CPU: AMD Opteron (TM) 852  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1-4  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 1024KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x1024 MB PC3200 CL3 ECC Reg  
 Disk Subsystem: SCSI, Seagate Cheetah Ultra320 ST336607LC, 10K rpm  
 Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition  
 Compiler: Intel C++ 8.0 build 20040714Z, Intel Fortran 8.1 for IA32 build 20041019Z, PGI Fortran compiler 5.2-4 for Windows XP, AMD Core Math library Version 2.1 (ACML), Microsoft Visual Studio .NET 7.0.9466 (libraries), MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
+ACML is linking with AMD Core Math Library V2.1
ONESTEP is set for all peak runs.
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler.
The Intel C++ 8.0 and the Intel Fortran 8.1 compilers are setup in the following order:
  "c:\program files\intel\fortran\compiler80\ia32\bin\ifortvars.bat"
  "c:\program files\intel\cpp\compiler80\ia32\bin\iclvars.bat"
To make sure that the correct libraries are selected, the following link option is
added for the peak runs where Intel Fortran 8.1 compiler is used:
  LDOPT = -Fe$@ -link -LIBPATH:"c:\program files\intel\fortran\compiler80\ia32\lib"
(denoted by +LIBPATH:INTEL8.1 in the optimization flags listed below)
Portability:
  178.galgel: -Mfixed
Baseline: C      : icl  -fast -arch:SSE2 -QaxW +FDO
Baseline: Fortran: pgf90 -fastsse -Mipa=fast,inlined
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices

Pogo Linux, PerformanceWare 3566, AMD Opteron (TM) 852

SPECfp\_rate2000 = 28.7

SPECfp\_rate\_base2000 = 27.3

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: May-2005 | Software Avail: Jan-2005

## Notes/Tuning Information (Continued)

Peak tuning:

```

168.wupwise:      pgf90 basepeak=yes
171.swim:         ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll0      +LIBPATH:INTEL8.1
172.mgrid:       pgf90 basepeak=yes
173.applu:        ifort -Qipo -O3 -QaxN -QxW +FDO -auto          +LIBPATH:INTEL8.1
177.mesa:         icl -Qipo -arch:SSE2 +FDO -Qunroll1 -Qansi_alias
                  -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
179.art:          icl -Qipo -Zp4 +FDO
183.quake:        icl basepeak=yes
178.galgel:       pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML
187.facerec:      ifort -Qipo -QxW +FDO -Qunroll3 +LIBPATH:INTEL8.1
                  -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ammp:         icl -Oa -arch:SSE2 -Zp4 -Qansi_alias
189.lucas:        ifort -Qipo -QxW -Qunroll1 +LIBPATH:INTEL8.1
191.fma3d:        ifort -Qipo -QaxN -QxW +FDO -Qansi-alias- +LIBPATH:INTEL8.1
200.sixtrack:     pgf90 basepeak=yes
301.apsi:         pgf90 basepeak=yes
Bios V2.33.1.1
All memory slots populated on CPU0.
Physical Address Extension (PAE) enabled

```