



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G4 (3.8GHz, Intel Xeon)

SPECfp2000 = 1885
SPECfp_base2000 = 1859

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	59.1	2708	59.1	2706	
171.swim	3100	132	2341	132	2343	
172.mgrid	1800	113	1592	113	1592	
173.applu	2100	135	1551	136	1544	
177.mesa	1400	84.3	1661	84.3	1661	
178.galgel	2900	78.7	3685	78.7	3686	
179.art	2600	62.8	4142	62.8	4142	
183.quake	1300	63.6	2043	52.6	2473	
187.facerec	1900	100	1899	99.4	1911	
188.amp	2200	173	1274	173	1274	
189.lucas	2000	96.8	2065	96.7	2068	
191.fma3d	2100	135	1556	135	1556	
200.sixtrack	1100	161	684	161	684	
301.apsi	2600	190	1367	190	1367	

Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048MB PC2-3200 Dual Rank
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)
Intel Fortran Compiler for 32-bit applications, (Version 8.1 Build 20050517Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning: -fast -Qansi_alias +FDO

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast -f77rtl +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: -fast +FDO ONESTEP=yes

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll11 -Qscalar_rep- -fpp +FDO ONESTEP=yes

188.amp: basepeak=1

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G4 (3.8GHz, Intel Xeon)

SPECfp2000 = 1885
SPECfp_base2000 = 1859

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled