



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 (AMD Opteron (TM) 854)

SPECint_rate2000 = 44.3
SPECint_rate_base2000 = 42.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	91.6	35.5	2	91.6	35.5
175.vpr	2	95.0	34.2	2	92.0	35.3
176.gcc	2	54.6	46.7	2	54.1	47.2
181.mcf	2	154	27.2	2	128	32.7
186.crafty	2	54.6	42.5	2	49.7	46.7
197.parser	2	104	40.1	2	104	40.1
252.eon	2	46.5	64.8	2	42.8	70.5
253.perlbnk	2	97.1	43.0	2	97.1	43.0
254.gap	2	56.5	45.1	2	56.5	45.1
255.vortex	2	67.7	65.2	2	67.8	65.0
256.bzip2	2	103	33.7	2	102	34.2
300.twolf	2	162	43.0	2	134	52.1

Hardware

CPU: AMD Opteron (TM) 854
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC3200 CL3.0
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler 8.0 Build 20031211Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 + FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL585 (AMD Opteron (TM) 854)

SPECint_rate2000 = 44.3
SPECint_rate_base2000 = 42.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:  -fast -Qunroll2
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
The start /b /wait /affinity command is used to bind CPU(s) to processes.