



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM

IBM eServer 326m, 1.8 GHz Dual Core AMD Opteron(tm) Processor 265

SPECint_rate2000 = 59.2

SPECint_rate_base2000 = 52.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	128	50.7	4	128	50.6
175.vpr	4	151	43.1	4	146	44.5
176.gcc	4	88.6	57.6	4	89.1	57.3
181.mcf	4	364	23.0	4	225	37.1
186.crafty	4	62.3	74.4	4	61.0	76.1
197.parser	4	209	39.9	4	170	49.2
252.eon	4	70.8	85.2	4	59.7	101
253.perlbnk	4	148	56.4	4	129	64.9
254.gap	4	95.6	53.4	4	90.7	56.3
255.vortex	4	104	84.5	4	92.7	95.1
256.bzip2	4	141	49.4	4	141	49.4
300.twolf	4	284	49.0	4	235	59.3

Hardware

CPU: Dual Core AMD Opteron(tm) Processor 265
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024GB PC3200
 Disk Subsystem: SCSI, 36GB 15K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP2 SLES 64 bit Kernel 2.6.5-7.191-smp (SP2)
 Compiler: PathScale EKO Compiler Suite, Release 2.2.1
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

Tested by IBM Corporation

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Base tuning for C programs: -Ofast +FDO

Base tuning for C++ programs: -Ofast +FDO

Portability flags:

186.crafty: -DLINUX_i386

252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64

253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL

-DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64

254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO

-DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64

255.vortex: -DSPEC_CPU2000_LP64

Peak tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO

175.vpr: -O3 -ipa -m32 +FDO

176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO

181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO

186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO

197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO

252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM

IBM eServer 326m, 1.8 GHz Dual Core AMD Opteron(tm) Processor 265

SPECint_rate2000 = 59.2

SPECint_rate_base2000 = 52.6

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

-OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exception
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO

```

BIOS Configuration Notes

Node Interleaving Disabled

Other Configuration Notes

Taskset utility used to bind process to CPU(s)