



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 560Q (1500 MHz, 1 CPU)

SPECint2000 = 1204
SPECint_base2000 = 1160

SPEC license #: 11 | Tested by: IBM | Test date: Nov-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	205	682	199	704	
175.vpr	1400	137	1021	134	1041	
176.gcc	1100	89.4	1230	88.7	1240	
181.mcf	1800	72.6	2481	86.4	2083	
186.crafty	1000	107	933	87.6	1142	
197.parser	1800	172	1044	169	1062	
252.eon	1300	106	1231	102	1273	
253.perlbmk	1800	234	770	213	845	
254.gap	1100	104	1058	102	1075	
255.vortex	1900	98.2	1934	86.6	2194	
256.bzip2	1500	133	1127	127	1177	
300.twolf	3000	229	1310	221	1357	

Hardware

CPU: POWER5+
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 1 core, 4 chips, 2 cores/chip (SMT off)
 CPU(s) orderable: 8,16
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified, shared (on chip)/chip
 L3 Cache: 2x36MB unified (off-chip)/QCM, 1 QCM/SUT
 Other Cache: None
 Memory: 16x2GB
 Disk Subsystem: 2x36GB SCSI, 15K RPM
 Other Hardware: None

Software

Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX
 File System: AIX/JFS2
 System State: Multi-user

Notes/Tuning Information

Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbmk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O5 -lhuu -qalign=natural
```

Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qarch=auto -qtune=auto -qfdpr -blpdata
          fdpr -q -O3
175.vpr: -qpdf1/pdf2
         -O5 -qfdpr -blpdata
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 560Q (1500 MHz, 1 CPU)

SPECint2000 = 1204
SPECint_base2000 = 1160

SPEC license #: 11 | Tested by: IBM | Test date: Nov-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

```

176.gcc:      fdpr -q -O3
              -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
181.mcf:      -qpdf1/pdf2
              -O4 -qarch=auto -qtune=auto -qalign=natural -blpdata
186.crafty:   -qpdf1/pdf2
              -O4 -qarch=auto -qtune=auto -qalign=natural -q64 -lhmu -blpdata
197.parser:   -qpdf1/pdf2
              -O4 -qfdpr -qarch=auto -qtune=auto -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:      -qpdf1/pdf2
              -O4 -qarch=auto -qtune=auto -qalign=natural
253.perlbnk:  -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhmu
254.gap:      -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:   -qpdf1/pdf2
              -O4 -qfdpr -qarch=auto -qtune=auto -lhmu -blpdata
              fdpr -q -O3
256.bzip2:    -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:    -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER version 5.3 with the 5300-03 Recommended Technology Level.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

QCM: Acronym for "Quad-Core Module" (Two dual-core processor chips + two L3-cache chips)

SUT: Acronym for "System Under Test"

Extended C: IBM XL C for AIX invoked as cc
C++: IBM XL C for AIX invoked as xlc

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=800 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \$$ \$$SPECUSERNUM; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

Seven cores were deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu

```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 560Q (1500 MHz, 1 CPU)

SPECint2000 = 1204

SPECint_base2000 = 1160

SPEC license #: 11 | Tested by: IBM | Test date: Nov-2005 | Hardware Avail: Feb-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

```
drmgr -r -c cpu  
drmgr -r -c cpu
```