



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL385 (AMD Opteron (TM) 285)

SPECfp2000 = 2124  
SPECfp\_base2000 = 1938

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Feb-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	59.4	2693	55.0	2909	[Bar chart showing ratio 2909]			
171.swim	3100	127	2441	122	2536	[Bar chart showing ratio 2536]			
172.mgrid	1800	105	1717	96.0	1874	[Bar chart showing ratio 1874]			
173.applu	2100	104	2013	91.8	2289	[Bar chart showing ratio 2289]			
177.mesa	1400	66.3	2111	61.5	2278	[Bar chart showing ratio 2278]			
178.galgel	2900	90.9	3192	81.2	3573	[Bar chart showing ratio 3573]			
179.art	2600	103	2521	72.0	3611	[Bar chart showing ratio 3611]			
183.quake	1300	81.4	1598	73.6	1767	[Bar chart showing ratio 1767]			
187.facerec	1900	74.7	2544	75.4	2521	[Bar chart showing ratio 2521]			
188.amp	2200	146	1511	135	1627	[Bar chart showing ratio 1627]			
189.lucas	2000	104	1928	91.1	2196	[Bar chart showing ratio 2196]			
191.fma3d	2100	130	1620	129	1632	[Bar chart showing ratio 1632]			
200.sixtrack	1100	126	871	121	909	[Bar chart showing ratio 909]			
301.apsi	2600	159	1636	150	1735	[Bar chart showing ratio 1735]			

### Hardware

CPU: AMD Opteron (TM) 285  
CPU MHz: 2600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 64KBI + 64KBD (on chip) per core  
Secondary Cache: 1024KB(I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x2048MB PC3200 CL3.0  
Disk Subsystem: 1x36GB 10K SAS  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP3  
SuSE kernel 2.6.5-7.244-default  
Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.3  
AMD Core Math Library 3.0.0  
File System: Linux/ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability flags:
 178.galgel: -fixedform
Peak tuning:
 168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
 171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
 173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO
 177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL385 (AMD Opteron (TM) 285)

SPECfp2000 = 2124  
SPECfp\_base2000 = 1938

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Feb-2006 Hardware Avail: Mar-2006 Software Avail: Feb-2006

## Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex-on RM_SOURCES=lapak.f90 +ACML +FDO
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.equake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2 -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammmp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
           -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
              -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Single-processor kernel was used