



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.46 GHz, Intel(R) Pentium(R) processor Extreme Edition 955)

SPECfp_rate2000 = 36.7

SPECfp_rate_base2000 = 36.6

SPEC license #: 13 Tested by: Intel(R) Corporation Test date: Mar-2006 Hardware Avail: Jan-2006 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	122	60.8	4	121	61.4
171.swim	4	442	32.6	4	442	32.6
172.mgrid	4	276	30.2	4	276	30.2
173.applu	4	330	29.5	4	318	30.7
177.mesa	4	179	36.3	4	179	36.3
178.galgel	4	224	60.2	4	225	59.9
179.art	4	237	50.8	4	237	50.8
183.quake	4	144	42.0	4	144	41.9
187.facerec	4	187	47.2	4	184	47.8
188.amp	4	370	27.6	4	366	27.9
189.lucas	4	294	31.6	4	292	31.8
191.fma3d	4	304	32.0	4	304	32.0
200.sixtrack	4	254	20.1	4	261	19.5
301.apsi	4	342	35.3	4	343	35.2

Hardware

CPU: Intel(R) Pentium(R) processor Extreme Edition 955(3.46 GHz, 1066 MHz bus)
CPU MHz: 3466
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD per core
Secondary Cache: 2MB(I+D) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 1 GB (2 512MB Micron MT16HTF6464AY-667B3 DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCO Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X1900 XTX PCI express

Software

Operating System: Windows XP Professional SP2
Compiler: Intel(R) C++ and Fortran Compiler 9.0 for 32-bit Build 20050430Z
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast shlw32M.lib +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo shlw32M.lib +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.46 GHz, Intel(R) Pentium(R) processor Extreme Edition 955)

SPECfp_rate2000 = 36.7

SPECfp_rate_base2000 = 36.6

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Mar-2006 | Hardware Avail: Jan-2006 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 03/2006

<http://www.intel.com/products/motherboard/D975XBX/index.htm>

The system bus runs at 1066 MHz