



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5080 processor, 3.73 GHz

SPECfp_rate2000 = 64.2

SPECfp_rate_base2000 = 64.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Mar-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	77.9	95.2	4	77.9	95.2
171.swim	4	293	49.0	4	293	49.0
172.mgrid	4	185	45.2	4	185	45.2
173.applu	4	209	46.6	4	209	46.6
177.mesa	4	73.7	88.1	4	73.7	88.1
178.galgel	4	88.9	151	4	88.9	151
179.art	4	69.9	173	4	69.9	173
183.quake	4	135	44.7	4	135	44.7
187.facerec	4	127	69.6	4	127	69.6
188.amp	4	165	61.7	4	165	61.7
189.lucas	4	197	47.1	4	197	47.1
191.fma3d	4	188	51.8	4	188	51.8
200.sixtrack	4	149	34.1	4	149	34.1
301.apsi	4	214	56.4	4	214	56.4

Hardware

CPU: Intel Xeon 5080 processor (3.73 GHz, 2x2MB L2, 1066 MHz system bus)
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDRII-RAM PC2-4200F (CAS 4-4-4)
Disk Subsystem: Seagate ST936701SS (SAS, 10 krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
for Fortran and C programs: -fast +FDO

Peak tuning flags
same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon 5080 processor, 3.73 GHz

SPECfp_rate2000 = 64.2

SPECfp_rate_base2000 = 64.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Mar-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1066 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>