



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G5 (3.73GHz, Intel Xeon Processor 5080)

SPECfp2000 = **1891**
SPECfp_base2000 = **1884**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	47.0	3408	46.9	3409	
171.swim	3100	121	2567	121	2566	
172.mgrid	1800	115	1571	115	1572	
173.applu	2100	122	1723	122	1723	
177.mesa	1400	87.3	1604	86.9	1612	
178.galgel	2900	78.7	3685	78.7	3685	
179.art	2600	59.7	4354	59.7	4354	
183.quake	1300	47.0	2765	47.0	2765	
187.facerec	1900	124	1535	124	1536	
188.amp	2200	198	1111	191	1155	
189.lucas	2000	123	1620	123	1625	
191.fma3d	2100	135	1551	135	1551	
200.sixtrack	1100	150	734	150	734	
301.apsi	2600	194	1344	194	1344	

Hardware

CPU: Intel Xeon Processor 5080 (3.73GHz, 2x2MB L2, 1066MHz bus)
CPU MHz: 3730
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8x2048MB PC2-5300F dual-rank
Disk Subsystem: 1x146GB 15K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smarheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for Fortran programs: -fast -Qansi_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML350 G5 (3.73GHz, Intel Xeon Processor 5080)

SPECfp2000 = 1891
SPECfp_base2000 = 1884

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

188. ammp: -fast -Qansi_alias +FDO
189. lucas: -fast
191. fma3d: basepeak=1
200. sixtrack: -fast +FDO
301. psi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology disabled