



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Acer Altos R720 (3.0 GHz Intel Xeon Processor 5160)

SPECfp_rate2000 = **81.0**
SPECfp_rate_base2000 = **81.0**

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	66.6	111	4	66.6	111
171.swim	4	266	54.2	4	266	54.2
172.mgrid	4	171	48.9	4	171	48.9
173.applu	4	182	53.7	4	182	53.7
177.mesa	4	47.8	136	4	47.8	136
178.galgel	4	60.6	222	4	60.6	222
179.art	4	52.9	228	4	52.9	228
183.equake	4	127	47.4	4	127	47.4
187.facerec	4	86.8	102	4	86.8	102
188.amp	4	117	87.3	4	117	87.3
189.lucas	4	171	54.4	4	171	54.4
191.fma3d	4	161	60.7	4	161	60.7
200.sixtrack	4	97.9	52.1	4	97.9	52.1
301.apsi	4	183	66.0	4	183	66.0

Hardware

CPU: Intel Xeon Processor 5160 (3.0 GHz, 4MB L2, 1333MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware:

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler: Intel C++ 9.1 for EM64T build 20060323 and Fortran Compiler 9.1 for EM64T build 20060323
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks
+FDO : PASS1= -prof_gen PASS2= -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks