



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3455 (AMD Opteron (TM) 2220 SE)

SPECint2000 = 1851

SPECint_base2000 = 1638

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	82.9	1689	82.7	1692	
175.vpr	1400	110	1276	105	1333	
176.gcc	1100	60.0	1835	60.1	1832	
181.mcf	1800	287	627	164	1101	
186.crafty	1000	41.4	2413	41.4	2415	
197.parser	1800	146	1233	115	1569	
252.eon	1300	43.8	2967	39.3	3310	
253.perlbnk	1800	99.8	1804	88.4	2036	
254.gap	1100	63.5	1732	63.5	1732	
255.vortex	1900	73.4	2588	68.6	2770	
256.bzip2	1500	99.6	1506	99.6	1506	
300.twolf	3000	214	1404	156	1924	

Hardware

CPU: AMD Opteron 2220 SE
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2GB, PC2-5300
 Disk Subsystem: SATA, 80GB 10K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.4
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3455 (AMD Opteron (TM) 2220 SE)

SPECint2000 = 1851

SPECint_base2000 = 1638

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```

186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
        -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
        -LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
        -fno-math-errno -IPA:plimit=10000 +FDO
254.gap: basepeak = true
255.vortex: -Ofast -OPT:goto=off -CG:p2align=on
        -GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2: basepeak = true
300.twolf: -O2 -CG:gcm=off:p2align_freq=100000
        -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
        -WOPT:mem_opnds=on -m32 +FDO

```