



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECfp\_rate2000 = 43.5  
SPECfp\_rate\_base2000 = 43.2

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Aug-2006 Hardware Avail: Aug-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	53.8	69.0	2	53.6	69.2
171.swim	2	234	30.7	2	234	30.7
172.mgrid	2	149	28.0	2	149	28.0
173.applu	2	173	28.2	2	173	28.2
177.mesa	2	62.0	52.4	2	61.8	52.5
178.galgel	2	63.1	107	2	62.6	107
179.art	2	51.4	117	2	51.3	118
183.equake	2	65.8	45.8	2	65.9	45.8
187.facerec	2	85.8	51.4	2	86.0	51.3
188.amp	2	151	33.8	2	138	36.9
189.lucas	2	139	33.5	2	139	33.5
191.fma3d	2	145	33.5	2	146	33.4
200.sixtrack	2	116	22.0	2	116	22.0
301.apsi	2	165	36.6	2	164	36.8

### Hardware

CPU: Intel Core 2 Duo processor E6600  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
 Secondary Cache: 4096KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x 1GB PC2-5300 5-5-5 2Rank SDRAM  
 Disk Subsystem: 1 x 160GB SATA 7200 RPM  
 Other Hardware: None

### Software

Operating System: Windows XP Professional, Service Pack 2  
 Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1,  
 - Build 20060519Z Package ID: W\_CC\_P\_9.1.025  
 Intel(R) Fortran Compiler for 32-bit app., Version 9.1,  
 - Build 20060519Z Package ID: W\_FC\_P\_9.1.025  
 Microsoft Visual Studio .NET 2003 (for libraries)  
 MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)  
 File System: FAT32  
 System State: Default

## Notes/Tuning Information

### Portability flags:

178.galgel: -FI /F32000000

### Feedback optimization:

+FDO: PASS1= -Qprof\_gen PASS2= -Qprof\_use

### Baseline Tuning Flags:

for C programs:  
 -fast +FDO shlW32M.lib  
 for Fortran programs:  
 -fast +FDO shlW32M.lib

### Peak Tuning Flags:

173.applu: basepeak=yes  
 168.wupwise: -fast +FDO  
 171.swim: -fast +FDO  
 172.mgrid: -fast +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers  
CELSIUS M450 (Intel Core 2 Duo processor E6600)

SPECfp\_rate2000 = 43.5  
SPECfp\_rate\_base2000 = 43.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
173.applu:    basepeak=yes
177.mesa:    -fast +FDO ONESTEP=yes
178.galgel:  -fast +FDO
179.art:     -fast +FDO shlW32M.lib
183.quake:  -fast +FDO shlW32M.lib
187.facerec: -fast +FDO
188.ampp:   -fast +FDO
189.lucas:   basepeak=yes
191.fma3d:  -fast +FDO
200.sixtrack: -fast +FDO
301.apsi:   -fast +FDO
```

### Extra Libraries:

```
shlW32M.lib = Microquill SmartHeap Library 8
see www.microquill.com
```

The system bus runs at 1066 MHz

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>