



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3455 (AMD Opteron (TM) 2214)

SPECfp2000 = 1882
SPECfp_base2000 = 1726

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	69.1	2314	61.2	2612	
171.swim	3100	124	2498	115	2707	
172.mgrid	1800	117	1536	105	1714	
173.applu	2100	116	1812	105	2004	
177.mesa	1400	80.5	1740	75.3	1859	
178.galgel	2900	102	2843	102	2837	
179.art	2600	117	2225	86.0	3023	
183.earthquake	1300	93.4	1391	85.4	1522	
187.facerec	1900	85.1	2231	83.5	2275	
188.amp	2200	169	1299	162	1360	
189.lucas	2000	105	1910	88.9	2250	
191.fma3d	2100	145	1453	146	1437	
200.sixtrack	1100	150	734	142	772	
301.apsi	2600	182	1431	169	1537	

Hardware

CPU: AMD Opteron 2214
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2GB, PC2-5300
 Disk Subsystem: SATA, 80GB 10K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.4
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization

C programs: -Ofast -WOPT:mem_opnds=on +FDO
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
 Portability Flags:
 178.galgel: -fixedform

Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3
 -OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3
 171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_arith=3:unroll_size=200
 -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2
 -WOPT:mem_opnds=on:aggstr=0
 173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
 -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3455 (AMD Opteron (TM) 2214)

SPECfp2000 = 1882
SPECfp_base2000 = 1726

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```
177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.earthquake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:   -Ofast -IPA:plimit=1500 -LNO:fusion=2
               -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.amp:       -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:     -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
               -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:      -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2
```